
imageio Documentation

Release 2.16.1

imageio contributors

Feb 28, 2022

CONTENTS

1	User Guide	3
1.1	Getting Started	3
1.2	Other Usage	13
2	Supported Formats	17
2.1	Formats by Plugin	17
2.2	Video Formats	18
2.3	All Formats	18
3	API Reference	25
3.1	Core API (Basic Usage)	25
3.2	Plugins & Backend Libraries (Advanced Usage)	32
4	Contributing	49
4.1	The ImageIO Plugin API	49
4.2	Small Changes to the Documentation	60
4.3	Large Changes to the Documentation	60
4.4	Fixing a Bug	61
4.5	Adding a new Feature	62
4.6	Webdesign	63
4.7	DevOps	63
4.8	Implementing a new Plugin	64
4.9	Adding a missing Format	72
4.10	Full Developer Setup	72
	Python Module Index	73
	Index	75

Imageio is a Python library that provides an easy interface to read and write a wide range of image data, including animated images, volumetric data, and scientific formats. It is cross-platform, runs on Python 3.5+, and is easy to install.

Main website: <https://imageio.readthedocs.io/>

Contents:

USER GUIDE

1.1 Getting Started

1.1.1 Installing imageio

Imageio is written in pure Python, so installation is easy. Imageio works on Python 3.5+. It also works on Pypy. Imageio depends on Numpy and Pillow. For some formats, imageio needs additional libraries/executables (e.g. ffmpeg), which imageio helps you to download/install.

To install imageio, use one of the following methods:

- If you are in a conda env: `conda install -c conda-forge imageio`
- If you have pip: `pip install imageio`
- Good old python `setup.py install`

After installation, checkout the *examples* and *user api*.

Still running Python 2.7? Read *here*.

1.1.2 Imageio Usage Examples

Some of these examples use Visvis to visualize the image data, but one can also use Matplotlib to show the images.

Imageio provides a range of *example images*, which can be used by using a URI like 'imageio:chelsea.png'. The images are automatically downloaded if not already present on your system. Therefore most examples below should just work.

Read an image of a cat

Probably the most important thing you'll ever need.

```
import imageio as iio

im = iio.imread('imageio:chelsea.png')
print(im.shape)
```

If the image is a GIF:

```
import imageio as iio

im = iio.get_reader('cat.gif')
for frame in im:
    print(frame.shape)  # Each frame is a numpy matrix
```

If the GIF is stored in memory:

```
import imageio as iio

im = iio.get_reader(image_bytes, '.gif')
```

Read from fancy sources

Imageio can read from filenames, file objects, http, zipfiles and bytes.

```
import imageio as iio
import visvis as vv

im = iio.imread('http://upload.wikimedia.org/wikipedia/commons/d/de/Wikipedia_Logo_1.0.
↳png')
vv.imshow(im)
```

Note: reading from HTTP and zipfiles works for many formats including png and jpeg, but may not work for all formats (some plugins “seek” the file object, which HTTP/zip streams do not support). In such a case one can download/extract the file first. For HTTP one can use something like `imageio.imread(imageio.core.urlopen(url).read(), '.gif')`.

Read all Images in a Folder

One common scenario is that you want to read all images in a folder, e.g. for a scientific analysis, or because these are all your training examples. Assuming the folder only contains image files, you can read it using a snippet like

```
import imageio as iio
from pathlib import Path

images = list()
for file in Path("path/to/folder").iterdir():
    im = iio.imread(file)
    images.append(im)
```

Iterate over frames in a movie

```
import imageio as iio

reader = iio.get_reader('imageio:cockatoo.mp4')
for i, im in enumerate(reader):
    print('Mean of frame %i is %1.1f' % (i, im.mean()))
```


Grab screenshot or image from the clipboard

(Screenshots are supported on Windows and OS X, clipboard on Windows only.)

```
import imageio as iio

im_screen = iio.imread('<screen>')
im_clipboard = iio.imread('<clipboard>')
```

Grab frames from your webcam

Use the special <video0> uri to read frames from your webcam (via the ffmpeg plugin). You can replace the zero with another index in case you have multiple cameras attached. You need to `pip install imageio-ffmpeg` in order to use this plugin.

```
import imageio as iio
import visvis as vv

reader = iio.get_reader('<video0>')
t = vv.imshow(reader.get_next_data(), clim=(0, 255))
for im in reader:
    vv.processEvents()
    t.SetData(im)
```

Convert a movie

Here we take a movie and convert it to gray colors. Of course, you can apply any kind of (image) processing to the image here ... You need to `pip install imageio-ffmpeg` in order to use the ffmpeg plugin.

```
import imageio as iio

reader = iio.get_reader('imageio:cockatoo.mp4')
fps = reader.get_meta_data()['fps']

writer = iio.get_writer('~/.cockatoo_gray.mp4', fps=fps)

for im in reader:
    writer.append_data(im[:, :, 1])
writer.close()
```

Read medical data (DICOM)

```
import imageio as iio
dirname = 'path/to/dicom/files'

# Read as loose images
ims = iio.mimread(dirname, 'DICOM')
# Read as volume
vol = iio.volread(dirname, 'DICOM')
```

(continues on next page)

(continued from previous page)

```
# Read multiple volumes (multiple DICOM series)
vols = iio.mvolread(dirname, 'DICOM')
```

Volume data

```
import imageio as iio
import visvis as vv

vol = iio.volread('imageio:stent.npz')
vv.volshow(vol)
```

Writing videos with FFMPEG and vaapi

Using vaapi (on Linux only) (intel only?) can help free up resources on your laptop while you are encoding videos. One notable difference between vaapi and x264 is that vaapi doesn't support the color format yuv420p.

Note, you will need ffmpeg compiled with vaapi for this to work.

```
import imageio as iio
import numpy as np

# All images must be of the same size
image1 = np.stack([imageio.imread('imageio:camera.png')] * 3, 2)
image2 = iio.imread('imageio:astronaut.png')
image3 = iio.imread('imageio:immunohistochemistry.png')

w = iio.get_writer('my_video.mp4', format='FFMPEG', mode='I', fps=1,
                  codec='h264_vaapi',
                  output_params=['-vaapi_device',
                                '/dev/dri/renderD128',
                                '-vf',
                                'format=gray|nv12,hwupload'],
                  pixelformat='vaapi_vld')

w.append_data(image1)
w.append_data(image2)
w.append_data(image3)
w.close()
```

A little bit of explanation:

- `output_params`
 - `vaapi_device` specifies the encoding device that will be used.
 - `vf` and `format` tell ffmpeg that it must upload to the dedicated hardware. Since vaapi only supports a subset of color formats, we ensure that the video is in either gray or nv12 before uploading it. The or operation is achieved with `|`.
- `pixelformat`: set to `'vaapi_vld'` to avoid a warning in ffmpeg.
- `codec`: the code you wish to use to encode the video. Make sure your hardware supports the chosen codec. If your hardware supports h265, you may be able to encode using `'hevc_vaapi'`

Writing to Bytes (Encoding)

You can convert ndimages into byte strings. For this, you have to explicitly specify the desired format, as a byte string doesn't carry any information about the format or color space to use. Since backends differ in the way this information should be provided, you also have to explicitly specify the backend (plugin) to use. Note that, if the backend supports writing to file-like objects, the entire process will happen without touching your file-system. If you, for example, want to write with pillow, you can use:

```
from imageio import v3 as iio

# load an example image
img = iio.imread('imageio:astronaut.png')

# png-encoded bytes string
# Note: defaults to RGB color space
png_encoded = iio.imwrite("<bytes>", img, plugin="pillow", format="PNG")

# jpg-encoded bytes string
# Note: defaults to RGB color space
jpg_encoded = iio.imwrite("<bytes>", img, plugin="pillow", format="JPEG")

# RGBA bytes string
# Important Note: omitting mode="RGBA" would result in a corrupted byte string
img = iio.imread('imageio:astronaut.png', mode="RGBA")
jpg_encoded = iio.imwrite("<bytes>", img, plugin="pillow", format="JPEG", mode="RGBA")
```

Writing to BytesIO

Similar to writing to byte strings, you can also write to BytesIO directly.

```
from imageio import v3 as iio
import io

# load an example image
img = iio.imread('imageio:astronaut.png')

# write as PNG
output = io.BytesIO()
iio.imwrite(output, img, plugin="pillow", format="PNG")

# write as JPG
output = io.BytesIO()
iio.imwrite(output, img, plugin="pillow", format="JPEG")
```

Optimizing a GIF using pygifsicle

When creating a GIF using `imageio` the resulting images can get quite heavy, as the created GIF is not optimized. This can be useful when the elaboration process for the GIF is not finished yet (for instance if some elaboration on specific frames stills need to happen), but it can be an issue when the process is finished and the GIF is unexpectedly big.

GIF files can be compressed in several ways, the most common one method (the one used here) is saving just the differences between the following frames. In this example, we apply the described method to a given GIF *my_gif* using `pygifsicle`, a porting of the general-purpose GIF editing command-line library `gifsicle`. To install `pygifsicle` and `gifsicle`, [read the setup on the project page](#): it boils down to installing the package using `pip` and following the console instructions:

```
pip install pygifsicle
```

Now, let's start by creating a gif using `imageio`:

```
import imageio as iio
import matplotlib.pyplot as plt

n = 100
gif_path = "test.gif"
frames_path = "{i}.jpg"

n = 100
plt.figure(figsize=(4,4))
for i, x in enumerate(range(n)):
    plt.scatter(x/n, x/n)
    plt.xlim(0, 1)
    plt.ylim(0, 1)
    plt.savefig("{i}.jpg".format(i=i))

with iio.get_writer(gif_path, mode='I') as writer:
    for i in range(n):
        writer.append_data(iio.imread(frames_path.format(i=i)))
```

This way we obtain a 2.5MB gif.

We now want to compress the created GIF. We can either overwrite the initial one or create a new optimized one: We start by importing the library method:

```
from pygifsicle import optimize

optimize(gif_path, "optimized.gif") # For creating a new one
optimize(gif_path) # For overwriting the original one
```

The new optimized GIF now weights 870KB, almost 3 times less.

Putting everything together:

```
import imageio as iio
import matplotlib.pyplot as plt
from pygifsicle import optimize

n = 100
gif_path = "test.gif"
```

(continues on next page)

(continued from previous page)

```
frames_path = "{i}.jpg"

n = 100
plt.figure(figsize=(4,4))
for i, x in enumerate(range(n)):
    plt.scatter(x/n, x/n)
    plt.xlim(0, 1)
    plt.ylim(0, 1)
    plt.savefig("{i}.jpg".format(i=i))

with iio.get_writer(gif_path, mode='I') as writer:
    for i in range(n):
        writer.append_data(iio.imread(frames_path.format(i=i)))

optimize(gif_path)
```

Reading Images from ZIP archives

Note: In the future, this syntax will change to better match the URI standard by using fragments. The updated syntax will be "Path/to/file.zip#path/inside/zip/to/image.png".

```
import imageio as iio

image = iio.imread("Path/to/file.zip/path/inside/zip/to/image.png")
```

Reading Multiple Files from a ZIP archive

Assuming there is only image files in the ZIP archive, you can iterate over them with a simple script like the one below.

```
import os
from zipfile import ZipFile
import imageio as iio

images = list()
with ZipFile("imageio.zip") as zf:
    for name in zf.namelist():
        im = iio.imread(name)
        images.append(im)
```

1.1.3 ImageResources

Reading images isn't always limited to simply loading a file from a local disk. Maybe you are writing a web application and you want to read images from HTTP, or your images are already in memory as a BytesIO object. Maybe you are doing machine learning and decided that it is smart to compress your images inside a ZIP file to reduce the IO bottleneck. All these are examples of different places where image data is stored (aka. resources).

ImageIO supports reading (and writing where applicable) for all of the above examples and more. To stay organized, we group all these sources/resources together and call them `ImageResource`. Often `ImageResources` are expressed as URIs though sometimes (e.g., in the case of byte streams) they can be python objects, too.

Here, you can find the documentation on what kind of `ImageResources` ImageIO currently supports together with documentation and an example on how to read/write them.

Files

Arguably the most common type of resource. You specify it using the path to the file, e.g.

```
img = iio.imread("path/to/my/image.jpg") # relative path
img = iio.imread("/path/to/my/image.jpg") # absolute path on Linux
img = iio.imread("C:\\path\\to\\my\\image.jpg") # absolute path on Windows
```

Notice that this is a convenience shorthand (since it is so common). Alternatively, you can use the full URI to the resource on your disk

```
img = iio.imread("file://path/to/my/image.jpg")
img = iio.imread("file:///path/to/my/image.jpg")
img = iio.imread("file://C:\\path\\to\\my\\image.jpg")
```

Byte Streams

ImageIO can directly handle (binary) file objects. This includes `BytesIO` objects (and subclasses thereof) as well as generic objects that implement `close` and a `read` and/or `write` function. Simply pass them into ImageIO the same way you would pass a URI:

```
file_handle = open("some/image.jpg", "rb")
img = iio.imread(file_handle)
```

Standard Images

Standard images are a curated dataset of pictures in different formats that you can use to test your pipelines. You can access them via the `imageio` scheme

```
img = iio.imread("imageio://chelsea.png")
```

A list of all currently available standard images can be found in the section on *Standard Images*.

Web Servers (http/https)

Note: This is primarily intended for publically available ImageResources. If your server requires authentication, you will have to download the ImageResource yourself before handing it over to ImageIO.

Reading http and https is provided directly by ImageIO. This means that ImageIO takes care of requesting and (if necessary) downloading the image and then hands the image to a compatible backend to do the reading itself. It works with any backend. If the backend supports file objects directly, this processes will happen purely in memory.

You can read from public web servers using a URL string

```
img = iio.imread("https://my-domain.com/path/to/some/image.gif")
```

File Servers (ftp/ftps)

Note: This is primarily intended for publically available ImageResources. If your server requires authentication, you will have to download the ImageResource yourself before handing it over to ImageIO.

Reading ftp and ftps is provided directly by ImageIO following the same logic as reading from web servers:

```
img = iio.imread("ftp://my-domain.com/path/to/some/image.gif")
```

Webcam

Note: To access your webcam you will need to have the ffmpeg backend installed:

```
pip install imageio[ffmpeg]
```

With ImageIO you can directly read images (frame-by-frame) from a webcam that is connected to the computer. To do this, you can use the special target:

```
img = iio.imread("<video0>")
```

If you have multiple video sources, you can replace the 0 with the respective number, e.g:

```
img = iio.imread("<video2>")
```

If you need many frames, e.g., because you want to process a stream, it is often much more performant to open the webcam once, keep it open, and read frames on-demand. You can find an example of this in the [list of examples](#).

Screenshots

Note: Taking screenshots are only supported on Windows and Mac.

ImageIO gives you basic support for taking screenshots via the special target `screen`:

```
img = iio.imread("<screen>")
```

Clipboard

Note: reading from clipboard is only supported on Windows.

ImageIO gives you basic support for reading from your main clipboard via the special target `clipboard`:

```
img = iio.imread("<clipboard>")
```

ZIP Archives

You can directly read ImageResources from within ZIP archives without extracting them. For this purpose ZIP archives are treated as normal folders; however, nested zip archives are not supported:

```
img = iio.imread("path/to/file.zip/abspath/inside/zipfile/to/image.png")
```

Note that in a future version of ImageIO the syntax for reading ZIP archives will be updated to use fragments, i.e., the path inside the zip file will become a URI fragment.

1.1.4 Bird's eye view on ImageIO

The aim of this page is to give you a high level overview of how ImageIO works under the hood. We think this is useful for two reasons:

1. If something doesn't work as it should, you need to know where to search for causes. The overview on this page aims to help you in this regard by giving you an idea of how things work, and - hence - where things may go sideways.
2. If you do find a bug and decide to report it, this page helps us establish some joint vocabulary so that we can quickly get onto the same page, figure out what's broken, and how to fix it.

Terminology

You can think of ImageIO in three parts that work in sequence in order to load an image.

ImageIO Core The user-facing APIs (legacy + v3) and a plugin manager. You send requests to `iio.core` and it uses a set of plugins (see below) to figure out which backend (see below) to use to fulfill your request. It does so by (intelligently) searching a matching plugin, or by sending the request to the plugin you specified explicitly.

Plugin A backend-facing adapter/wrapper that responds to a request from `iio.core`. It can convert a request that comes from `iio.core` into a sequence of instructions for the backend that fulfill the request (eg., `read/write/iter`). A plugin is also aware if its backend is or isn't installed and handles this case appropriately, e.g., it deactivates itself if the backend isn't present.

Backend Library A (potentially 3d party) library that can read and/or write images or image-like objects (videos, etc.). Every backend is optional, so it is up to you to decide which backends to install depending on your needs. Examples for backends are pillow, tiff file, or ffmpeg.

ImageResource A blob of data that contains image data. Typically, this is a file on your drive that is read by ImageIO. However, other sources such as HTTP or file objects are possible, too.

Issues

In this repo, we maintain ImageIO Core as well as all the plugins. If you find a bug or have a problem with either the core or any of the plugins, please open a new issue [here](#).

If you find a bug or have problems with a specific backend, e.g. reading is very slow, please file an issue upstream (the place where the backend is maintained). When in doubt, you can always ask us, and we will redirect you appropriately.

New Plugins

If you end up writing a new plugin, we very much welcome you to contribute it back to us so that we can offer as expansive a list of backends and supported formats as possible. In return, we help you maintain the plugin - note: a plugin is typically different from the backend - and make sure that changes to ImageIO don't break your plugin. This we can only guarantee if it is part of the codebase, because we can (a) write unit tests for it and (b) update your plugin to take advantage of new features. That said, we generally try to be backward-compatible whenever possible.

The backend itself lives elsewhere, usually in a different repository. Not vendoring backends and storing a copy here keeps things lightweight yet powerful. We can, first of all, directly access any new updates or features that a backend may introduce. Second, we avoid forcing users that won't use a specific backend to go through its, potentially complicated, installation process.

1.2 Other Usage

1.2.1 Imageio Standard Images

Imageio provides a number of standard images. These include classic 2D images, as well as animated and volumetric images. To the best of our knowledge, all the listed images are in public domain.

The image names can be loaded by using a special URI, e.g. `imread('imageio:astronaut.png')`. The images are automatically downloaded (and cached in your appdata directory).

```
{% for name in ordered_keys %} * {{name}}: {{images[name]}} {% endfor %}
```

1.2.2 Imageio command line scripts

This page lists the command line scripts provided by imageio. To see all options for a script, execute it with the `--help` option, e.g. `imageio_download_bin --help`.

- `imageio_download_bin`: Download binary dependencies for imageio plugins to the users application data directory. This script accepts the parameter `--package-dir` which will download the binaries to the directory where imageio is installed. This option is useful when freezing an application with imageio. It is supported out-of-the-box by PyInstaller version $\geq 3.2.2$.
- `imageio_remove_bin`: Remove binary dependencies of imageio plugins from all directories managed by imageio. This script is useful when there is a corrupt binary or when the user prefers the system binary over the binary provided by imageio.

1.2.3 Imageio environment variables

This page lists the environment variables that imageio uses. You can set these to control some of imageio's behavior. Each operating system has its own way for setting environment variables, but to set a variable for the current Python process use `os.environ['IMAGEIO_VAR_NAME'] = 'value'`.

- **IMAGEIO_NO_INTERNET**: If this value is “1”, “yes”, or “true” (case insensitive), makes imageio not use the internet connection to retrieve files (like libraries or sample data). Some plugins (e.g. freeimage and ffmpeg) will try to use the system version in this case.
- **IMAGEIO_FFMPEG_EXE**: Set the path to the ffmpeg executable. Set to simply “ffmpeg” to use your system ffmpeg executable.
- **IMAGEIO_FREEIMAGE_LIB**: Set the path to the freeimage library. If not given, will prompt user to download the freeimage library.
- **IMAGEIO_FORMAT_ORDER**: Determine format preference. E.g. setting this to “TIFF, -FI” will prefer the FreeImage plugin over the Pillow plugin, but still prefer TIFF over that. Also see the `formats.sort()` method.
- **IMAGEIO_REQUEST_TIMEOUT**: Set the timeout of http/ftp request in seconds. If not set, this defaults to 5 seconds.
- **IMAGEIO_USERDIR**: Set the path to the default user directory. If not given, imageio will try `~` and if that's not available `/var/tmp`.

1.2.4 Transitioning from Scipy's imread

Scipy has [deprecated](#) their image I/O functionality.

This document is intended to help people coming from Scipy to adapt to ImageIO's [imread](#) function. We recommend reading the [user api](#) and checking out some [examples](#) to get a feel of ImageIO.

ImageIO makes use of a variety of backends to support reading images (and volumes/movies) from many different formats. One of these backends is Pillow, which is the same library as used by Scipy's `imread`. This means that all image formats that were supported by scipy are supported by ImageIO. At the same time, Pillow is not the only backend of ImageIO, and those other backends give you access to additional formats. To manage this, ImageIO automatically selects the right backend to use based on the source to read (which you can of course control manually, should you wish to do so).

In short terms: In most places where you used Scipy's `imread`, ImageIO's `imread` is a drop-in replacement and ImageIO provides the same functionality as Scipy in these cases. In some cases, you will need to update the keyword arguments used.

- Instead of `mode`, use the `pilmode` keyword argument.
- Instead of `flatten`, use the `as_gray` keyword argument.
- The documentation for the above arguments is not on `imread`, but on the docs of the individual plugins, e.g. [Pillow](#).
- ImageIO's functions all return numpy arrays, albeit as a subclass (so that meta data can be attached).

1.2.5 Depreciating Python 2.7

Python 2.7 is deprecated from 2020. For more information on the scientific Python ecosystem's transition to Python3 only, see the [python3-statement](#).

Imageio 2.6.x is the last release to support Python 2.7. This release will remain available on Pypi and conda-forge. The *py2* branch may be used to continue supporting 2.7, but one should not expect (free) contributions from the imageio developers.

For more information on porting your code to run on Python 3, see the [python3-howto](#).

1.2.6 Freezing ImageIO

When freezing ImageIO you need to make sure that you are collecting the plugins you need in addition to the core library. This will not happen automagically, because plugins are lazy-loaded upon first use for better platform support and reduced loading times. This lazy-loading is an interesting case as (1) these plugins are exactly the kind of thing that *PyInstaller* tries desperately to avoid collecting to minimize package size and (2) these plugins are - by themselves - super lightweight and won't bloat the package.

To add plugins to the application your first option is to add all of imageio to your package, which will also include the plugins. This can be done by using a command-line switch when calling pyinstaller that will gather all plugins:

```
pyinstaller --collect-submodules imageio <entry_script.py>
```

Alternatively, if you want to limit the plugins used, you can include them individually using `--hidden-import`:

```
pyinstaller --hidden-import imageio.plugins.<plugin> <entry_script.py>
```

In addition, some plugins (e.g., *ffmpeg*) make use of external programs, and for these, you will need to take extra steps to also include necessary [binaries](#). If you can't make it work, feel free to submit a [new issue](#), so that we can see how to improve this documentation further.

SUPPORTED FORMATS

Note: If you just want to know if a specific extension/format is supported you can search this page using Ctrl+F and then type the name of the extension or format.

ImageIO reads and writes images by delegating your request to one of many backends. Example backends are pillow, ffmpeg, tiff file among others. Each backend supports its own set of formats, which is how ImageIO manages to support so many of them.

To help you navigate this format jungle, ImageIO provides various curated lists of formats depending on your use-case

2.1 Formats by Plugin

Below you can find a list of each plugin that exists in ImageIO together with the formats that this plugin supports. This can be useful, for example, if you have to decide which plugins to install and/or depend on in your project.

FreeImage tif, tiff, jpeg, jpg, bmp, png, bw, dds, gif, ico, j2c, j2k, jp2, pbm, pcd, PCX, pgm, ppm, psd, ras, rgb, rgba, sgi, tga, xbm, xpm, pic, raw, 3fr, arw, bay, bmq, cap, cine, cr2, crw, cs1, cut, dc2, dcr, dng, drf, dsc, erf, exr, fff, g3, hdp, hdr, ia, iff, iiq, jif, jng, jpe, jxr, k25, kc2, kdc, koa, lbm, mdc, mef, mos, mrw, nef, nrw, orf, pct, pef, pfm, pict, ptx, pxn, qtk, raf, rdc, rw2, rwl, rwz, sr2, srf, srw, sti, targa, wap, wbm, wbmp, wdp, webp

Pillow tif, tiff, jpeg, jpg, bmp, png, bw, dds, gif, ico, j2c, j2k, jp2, pbm, pcd, PCX, pgm, ppm, psd, ras, rgb, rgba, sgi, tga, xbm, xpm, fit, fits, bufr, CLIPBOARDGRAB, cur, dcx, DIB, emf, eps, flc, fli, fpx, ftc, ftu, gbr, grib, h5, hdf, icns, iim, im, IMT, jfif, jpc, jpf, jpx, MCIDAS, mic, mpo, msp, ps, pxr, SCREENGRAB, SPIDER, wmf, XVTHUMB

ITK tif, tiff, jpeg, jpg, bmp, png, pic, img, lsm, dcm, dicom, gdc, gipl, hdf5, hdr, img.gz, ipl, mgh, mha, mhd, mnc, mnc2, nhdr, nia, nii, nii.gz, nrrd, vtk

FFMPEG avi, mkv, mov, mp4, mpeg, mpg, WEBCAM, webm, wmv

GDAL tif, tiff, jpeg, jpg, img, ecw

tiff file tif, tiff, lsm, stk

FITS fit, fits, fts, fz

DICOM dcm, ct, mri

Lytro raw, lfp, lfr

FEI/SEM tif, tiff

Numpy npz

BSDF bsdf

SPE spe

SWF swf

2.2 Video Formats

Below you can find an alphabetically sorted list of the video extensions/formats that ImageIO is aware of. If an extension is listed here, it is supported. If an extension is not listed here, it may still be supported if one of the backends supports the extension/format. If you encounter the latter, please [create a new issue](#) so that we can keep below list up to date and add support for any missing formats.

Each entry in the list below follows the following format:

```
<extension> (<format name>): <plugin> <plugin> ...
```

where <plugin> is the name of a plugin that can handle the format. If you wish to use a specific plugin to load a format, you would use the name as specified. For example, if you have a MOV file that you wish to open with FFMPEG and the <plugin> is called FFMPEG you would call:

```
io.imread("image.mov", format="FFMPEG")
```

Format List

Note: To complete this list we are looking for each format's full name and a link to the spec. If you come across this information, please consider sharing it by [creating a new issue](#).

- **.avi** (Audio Video Interleave): [FFMPEG](#)
- **.gif** (Graphics Interchange Format): [pillow GIF-PIL](#)
- **.mkv** (Matroska Multimedia Container): [FFMPEG](#)
- **.mov** (QuickTime File Format): [FFMPEG](#)
- **.mp4** (MPEG-4 Part 14): [FFMPEG](#)
- **.mpeg** (Moving Picture Experts Group): [FFMPEG](#)
- **.mpg** (Moving Picture Experts Group): [FFMPEG](#)
- **.webm**: [FFMPEG](#)
- **.wmv** (Windows Media Video): [FFMPEG](#)

2.3 All Formats

Below you can find an alphabetically sorted list of *all* extensions/file-formats that ImageIO is aware of. If an extension is listed here, it is supported. If an extension is not listed here, it may still be supported if one of the backends supports the extension/format. If you encounter the latter, please [create a new issue](#) so that we can keep below list up to date and add support for any missing formats.

Each entry in the list below follows the following format:

```
extension (format_name): plugin1 plugin2 ...
```

where the plugins refer to imageio plugins that can handle the format. If you wish to use a specific plugin to load a format, you would use the name as specified here. For example, if you have a PNG file that you wish to open with pillow you would call:

```
iiio.imread("image.png", format="PNG-PIL")
```

Format List

Note: To complete this list we are looking for each format's full name and a link to the spec. If you come across this information, please consider sharing it by [creating a new issue](#).

- **.3fr** (Hasselblad raw): *RAW-FI*
- **.DIB** (Windows Bitmap): *pillow DIB-PIL*
- **.IMT** (IM Tools): *pillow IMT-PIL*
- **.MCIDAS** (McIdas area file): *pillow MCIDAS-PIL*
- **.PCX** (Zsoft Paintbrush): *pillow PCX-FI PCX-PIL*
- **.SPIDER**: *pillow SPIDER-PIL*
- **.XVTHUMB** (Thumbnail Image): *pillow XVTHUMB-PIL*
- **.apng** (Animated Portable Network Graphics): *pillow*
- **.arw** (Sony alpha): *RAW-FI*
- **.avi** (Audio Video Interleave): *FFMPEG*
- **.bay** (Casio raw format): *RAW-FI*
- **.bmp** (Bitmap): *pillow BMP-PIL BMP-FI ITK*
- **.bm3** (Re-Volt mipmap): *RAW-FI*
- **.bsdf** (Binary Structured Data Format): *BSDF*
- **.bufr** (Binary Universal Form for the Representation of meteorological data): *pillow BUFR-PIL*
- **.bw** (Silicon Graphics Image): *pillow SGI-PIL SGI-FI*
- **.cap** (Scirra Construct): *RAW-FI*
- **.cine** (AMETEK High Speed Camera Format): *RAW-FI*
- **.cr2**: *RAW-FI*
- **.crw**: *RAW-FI*
- **.cs1**: *RAW-FI*
- **.ct** (Computerized Tomography): *DICOM*
- **.cur** (Windows Cursor Icons): *pillow CUR-PIL*
- **.cut** (Dr. Halo): *CUT-FI*
- **.dc2**: *RAW-FI*

- **.dcm** (DICOM file format): *DICOM ITK*
- **.dcr**: *RAW-FI*
- **.dcx** (Intel DCX): *pillow DCX-PIL*
- **.dds** (DirectX Texture Container): *pillow DDS-FI DDS-PIL*
- **.dicom** (DICOM file format): *ITK*
- **.dng**: *RAW-FI*
- **.drf**: *RAW-FI*
- **.dsc**: *RAW-FI*
- **.ecw** (Enhanced Compression Wavelet): *GDAL*
- **.emf** (Windows Metafile): *pillow WMF-PIL*
- **.eps** (Encapsulated Postscript): *pillow EPS-PIL*
- **.erf**: *RAW-FI*
- **.exr** (ILM OpenEXR): *EXR-FI*
- **.fff**: *RAW-FI*
- **.fit** (Flexible Image Transport System File): *pillow FITS-PIL FITS*
- **.fits** (Flexible Image Transport System File): *pillow FITS-PIL FITS*
- **.flc** (Autodesk FLC Animation): *pillow FLI-PIL*
- **.fli** (Autodesk FLI Animation): *pillow FLI-PIL*
- **.fpx** (Kodak FlashPix): *pillow FPX-PIL*
- **.ftc** (Independence War 2: Edge Of Chaos Texture Format): *pillow FTEX-PIL*
- **.fts** (Flexible Image Transport System File): *FITS*
- **.ftu** (Independence War 2: Edge Of Chaos Texture Format): *pillow FTEX-PIL*
- **.fz** (Flexible Image Transport System File): *FITS*
- **.g3** (Raw fax format CCITT G.3): *G3-FI*
- **.gbr** (GIMP brush file): *pillow GBR-PIL*
- **.gdcm** (Grassroots DICOM): *ITK*
- **.gif** (Graphics Interchange Format): *pillow GIF-PIL*
- **.gipl** (UMDS GIPL): *ITK*
- **.grib** (gridded meteorological data): *pillow GRIB-PIL*
- **.h5** (Hierarchical Data Format 5): *pillow HDF5-PIL*
- **.hdf** (Hierarchical Data Format 5): *pillow HDF5-PIL*
- **.hdf5** (Hierarchical Data Format 5): *ITK*
- **.hdp** (JPEG Extended Range): *JPEG-XR-FI*
- **.hdr** (High Dynamic Range Image): *HDR-FI ITK*
- **.ia**: *RAW-FI*
- **.icns** (Mac OS Icon File): *pillow ICNS-PIL*

- **.ico** (Windows Icon File): *pillow* ICO-FI *ICO-PIL*
- **.iff** (ILBM Interleaved Bitmap): *IFF-FI*
- **.iim** (IPTC/NAA): *pillow* IPTC-PIL
- **.iiq**: *RAW-FI*
- **.im** (IFUNC Image Memory): *pillow* IM-PIL
- **.img**: *ITK GDAL*
- **.img.gz**: *ITK*
- **.ipl** (Image Processing Lab): *ITK*
- **.j2c** (JPEG 2000): *pillow* J2K-FI *JPEG2000-PIL*
- **.j2k** (JPEG 2000): *pillow* J2K-FI *JPEG2000-PIL*
- **.jffif** (JPEG): *pillow* JPEG-PIL
- **.jif** (JPEG): *JPEG-FI*
- **.jng** (JPEG Network Graphics): *JNG-FI*
- **.jp2** (JPEG 2000): *pillow* JP2-FI *JPEG2000-PIL*
- **.jpc** (JPEG 2000): *pillow* JPEG2000-PIL
- **.jpe** (JPEG): *pillow* JPEG-FI *JPEG-PIL*
- **.jpeg** (Joint Photographic Experts Group): *pillow* JPEG-PIL *JPEG-FI* *ITK GDAL*
- **.jpf** (JPEG 2000): *pillow* JPEG2000-PIL
- **.jpg** (Joint Photographic Experts Group): *pillow* JPEG-PIL *JPEG-FI* *ITK GDAL*
- **.jpx** (JPEG 2000): *pillow* JPEG2000-PIL
- **.jxr** (JPEG Extended Range): *JPEG-XR-FI*
- **.k25**: *RAW-FI*
- **.kc2**: *RAW-FI*
- **.kdc**: *RAW-FI*
- **.koa** (C64 Koala Graphics): *KOALA-FI*
- **.lbm** (ILBM Interleaved Bitmap): *IFF-FI*
- **.lfp** (Lytro F01): *LYTRO-LFP*
- **.lfr** (Lytro Illum): *LYTRO-LFR*
- **.lsm** (ZEISS LSM): *ITK TIFF*
- **.mdc**: *RAW-FI*
- **.mef**: *RAW-FI*
- **.mgh** (FreeSurfer File Format): *ITK*
- **.mha** (ITK MetaImage): *ITK*
- **.mhd** (ITK MetaImage Header): *ITK*
- **.mic** (Microsoft Image Composer): *pillow* MIC-PIL
- **.mkv** (Matroska Multimedia Container): *FFMPEG*

- **.mnc** (Medical Imaging NetCDF): *ITK*
- **.mnc2** (Medical Imaging NetCDF 2): *ITK*
- **.mos** (Leaf Raw Image Format): *RAW-FI*
- **.mov** (QuickTime File Format): *FFMPEG*
- **.mp4** (MPEG-4 Part 14): *FFMPEG*
- **.mpeg** (Moving Picture Experts Group): *FFMPEG*
- **.mpg** (Moving Picture Experts Group): *FFMPEG*
- **.mpo** (JPEG Multi-Picture Format): *pillow MPO-PIL*
- **.mri** (Magnetic resonance imaging): *DICOM*
- **.mrw**: *RAW-FI*
- **.msp** (Windows Paint): *pillow MSP-PIL*
- **.nef**: *RAW-FI*
- **.nhdr**: *ITK*
- **.nia**: *ITK*
- **.nii**: *ITK*
- **.nii.gz** (nii.gz): *ITK*
- **.npz** (Numpy Array): *NPZ*
- **.nrrd**: *ITK*
- **.nrw**: *RAW-FI*
- **.orf**: *RAW-FI*
- **.pbm** (Portable Bitmap): *PGM-FI PGMRAW-FI*
- **.pbm** (Pbmplus image): *pillow PPM-PIL*
- **.pbm** (Pbmplus image): *pillow PPM-PIL PPM-FI*
- **.pcd** (Kodak PhotoCD): *pillow PCD-FI PCD-PIL*
- **.pct** (Macintosh PICT): *PICT-FI*
- **.pef**: *RAW-FI*
- **.pfm**: *PFM-FI*
- **.pgm** (Portable Greymap): *PGM-FI PGMRAW-FI*
- **.pic** (Macintosh PICT): *PICT-FI ITK*
- **.pict** (Macintosh PICT): *PICT-FI*
- **.png** (Portable Network Graphics): *pillow PNG-PIL PNG-FI ITK*
- **.ppm** (Pbmplus image): *pillow PPM-PIL*
- **.ppm** (Portable Pixelmap (ASCII)): *PPM-FI*
- **.ppm** (Portable Pixelmap (Raw)): *PPMRAW-FI*
- **.ps** (Ghostscript): *pillow EPS-PIL*
- **.psd** (Adobe Photoshop 2.5 and 3.0): *pillow PSD-PIL PSD-FI*

- **.ptx**: *RAW-FI*
- **.pxn**: *RAW-FI*
- **.pxr** (PIXAR raster image): *pillow PIXAR-PIL*
- **.qtk**: *RAW-FI*
- **.raf**: *RAW-FI*
- **.ras** (Sun Raster File): *pillow SUN-PIL RAS-FI*
- **.raw**: *RAW-FI LYTRO-ILLUM-RAW LYTRO-F01-RAW*
- **.rdc**: *RAW-FI*
- **.rgb** (Silicon Graphics Image): *pillow SGI-PIL*
- **.rgba** (Silicon Graphics Image): *pillow SGI-PIL*
- **.rw2**: *RAW-FI*
- **.rwl**: *RAW-FI*
- **.rwz**: *RAW-FI*
- **.sgi** (Silicon Graphics Image): *pillow SGI-PIL*
- **.spe** (SPE File Format): *SPE*
- **.sr2**: *RAW-FI*
- **.srf**: *RAW-FI*
- **.srw**: *RAW-FI*
- **.sti**: *RAW-FI*
- **.stk**: *TIFF*
- **.swf** (Shockwave Flash): *SWF*
- **.targa** (Truevision TGA): *TARGA-FI*
- **.tga** (Truevision TGA): *pillow TGA-PIL TARGA-FI*
- **.tif** (Tagged Image File): *TIFF pillow TIFF-PIL TIFF-FI FEI ITK GDAL*
- **.tiff** (Tagged Image File Format): *TIFF pillow TIFF-PIL TIFF-FI FEI ITK GDAL*
- **.vtk**: *ITK*
- **.wap** (Wireless Bitmap): *WBMP-FI*
- **.wbm** (Wireless Bitmap): *WBMP-FI*
- **.wbmp** (Wireless Bitmap): *WBMP-FI*
- **.wdp** (JPEG Extended Range): *JPEG-XR-FI*
- **.webm**: *FFMPEG*
- **.webp** (Google WebP): *WEBP-FI*
- **.wmf** (Windows Meta File): *pillow WMF-PIL*
- **.wmv** (Windows Media Video): *FFMPEG*
- **.xbm** (X11 Bitmap): *pillow XBM-PIL XBM-FI*
- **.xpm** (X11 Pixel Map): *pillow XPM-PIL XPM-FI*

API REFERENCE

ImageIO's API follows the usual idea of choosing sensible defaults for the average use, but giving you fine grained control

3.1 Core API (Basic Usage)

The API documented in this section is shared by all plugins

3.1.1 Core API v2.9

These functions represent imageio's main interface for the user. They provide a common API to read and write image data for a large variety of formats. All read and write functions accept keyword arguments, which are passed on to the backend that does the actual work. To see what keyword arguments are supported by a specific format, use the [help\(\)](#) function.

Note: All read-functions return images as numpy arrays, and have a `meta` attribute; the meta-data dictionary can be accessed with `im.meta`. To make this work, imageio actually makes use of a subclass of `np.ndarray`. If needed, the image can be converted to a plain numpy array using `np.asarray(im)`.

`imageio.help(name=None)`

Print the documentation of the format specified by name, or a list of supported formats if name is omitted.

Parameters

name [str] Can be the name of a format, a filename extension, or a full filename. See also the [formats page](#).

`imageio.show_formats()`

Show a nicely formatted list of available formats

Functions for reading

<code>imageio.imread(uri[, format])</code>	Reads an image from the specified file.
<code>imageio.mimread(uri[, format, memtest])</code>	Reads multiple images from the specified file.
<code>imageio.volread(uri[, format])</code>	Reads a volume from the specified file.
<code>imageio.mvolread(uri[, format, memtest])</code>	Reads multiple volumes from the specified file.

imageio.imread

`imageio.imread(uri, format=None, **kwargs)`

Reads an image from the specified file. Returns a numpy array, which comes with a dict of meta data at its ‘meta’ attribute.

Note that the image data is returned as-is, and may not always have a dtype of uint8 (and thus may differ from what e.g. PIL returns).

Parameters

uri [{str, pathlib.Path, bytes, file}] The resource to load the image from, e.g. a filename, pathlib.Path, http address or file object, see the docs for more info.

format [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.

kwargs [...] Further keyword arguments are passed to the reader. See [help\(\)](#) to see what arguments are available for a particular format.

imageio.mimread

`imageio.mimread(uri, format=None, memtest='256MB', **kwargs)`

Reads multiple images from the specified file. Returns a list of numpy arrays, each with a dict of meta data at its ‘meta’ attribute.

Parameters

uri [{str, pathlib.Path, bytes, file}] The resource to load the images from, e.g. a filename, pathlib.Path, http address or file object, see the docs for more info.

format [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.

memtest [{bool, int, float, str}] If truthy, this function will raise an error if the resulting list of images consumes greater than the amount of memory specified. This is to protect the system from using so much memory that it needs to resort to swapping, and thereby stall the computer. E.g. `mimread('hunger_games.avi')`.

If the argument is a number, that will be used as the threshold number of bytes.

If the argument is a string, it will be interpreted as a number of bytes with SI/IEC prefixed units (e.g. ‘1kB’, ‘250MiB’, ‘80.3YB’).

- Units are case sensitive
- k, M etc. represent a 1000-fold change, where Ki, Mi etc. represent 1024-fold
- The “B” is optional, but if present, must be capitalised

If the argument is True, the default will be used, for compatibility reasons.

Default: '256MB'

kwargs [...] Further keyword arguments are passed to the reader. See [help\(\)](#) to see what arguments are available for a particular format.

imageio.volread

`imageio.volread(uri, format=None, **kwargs)`

Reads a volume from the specified file. Returns a numpy array, which comes with a dict of meta data at its 'meta' attribute.

Parameters

uri [{str, pathlib.Path, bytes, file}] The resource to load the volume from, e.g. a filename, pathlib.Path, http address or file object, see the docs for more info.

format [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.

kwargs [...] Further keyword arguments are passed to the reader. See [help\(\)](#) to see what arguments are available for a particular format.

imageio.mvolread

`imageio.mvolread(uri, format=None, memtest='1GB', **kwargs)`

Reads multiple volumes from the specified file. Returns a list of numpy arrays, each with a dict of meta data at its 'meta' attribute.

Parameters

uri [{str, pathlib.Path, bytes, file}] The resource to load the volumes from, e.g. a filename, pathlib.Path, http address or file object, see the docs for more info.

format [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.

memtest [{bool, int, float, str}] If truthy, this function will raise an error if the resulting list of images consumes greater than the amount of memory specified. This is to protect the system from using so much memory that it needs to resort to swapping, and thereby stall the computer. E.g. `mimread('hunger_games.avi')`.

If the argument is a number, that will be used as the threshold number of bytes.

If the argument is a string, it will be interpreted as a number of bytes with SI/IEC prefixed units (e.g. '1kB', '250MiB', '80.3YB').

- Units are case sensitive
- k, M etc. represent a 1000-fold change, where Ki, Mi etc. represent 1024-fold
- The "B" is optional, but if present, must be capitalised

If the argument is True, the default will be used, for compatibility reasons.

Default: '1GB'

kwargs [...] Further keyword arguments are passed to the reader. See [help\(\)](#) to see what arguments are available for a particular format.

Functions for writing

<code>imageio.imwrite(uri, im[, format])</code>	Write an image to the specified file.
<code>imageio.mimwrite(uri, ims[, format])</code>	Write multiple images to the specified file.
<code>imageio.volwrite(uri, vol[, format])</code>	Write a volume to the specified file.
<code>imageio.mvolwrite(uri, vols[, format])</code>	Write multiple volumes to the specified file.

imageio.imwrite

`imageio.imwrite(uri, im, format=None, **kwargs)`

Write an image to the specified file.

Parameters

uri [{str, pathlib.Path, file}] The resource to write the image to, e.g. a filename, pathlib.Path or file object, see the docs for more info.

im [numpy.ndarray] The image data. Must be NxM, NxMx3 or NxMx4.

format [str] The format to use to write the file. By default imageio selects the appropriate for you based on the filename and its contents.

kwargs [...] Further keyword arguments are passed to the writer. See [help\(\)](#) to see what arguments are available for a particular format.

imageio.mimwrite

`imageio.mimwrite(uri, ims, format=None, **kwargs)`

Write multiple images to the specified file.

Parameters

uri [{str, pathlib.Path, file}] The resource to write the images to, e.g. a filename, pathlib.Path or file object, see the docs for more info.

ims [sequence of numpy arrays] The image data. Each array must be NxM, NxMx3 or NxMx4.

format [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.

kwargs [...] Further keyword arguments are passed to the writer. See [help\(\)](#) to see what arguments are available for a particular format.

imageio.volwrite

`imageio.volwrite(uri, vol, format=None, **kwargs)`

Write a volume to the specified file.

Parameters

uri [{str, pathlib.Path, file}] The resource to write the image to, e.g. a filename, pathlib.Path or file object, see the docs for more info.

vol [numpy.ndarray] The image data. Must be NxMxL (or NxMxLxK if each voxel is a tuple).

format [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.

kwargs [...] Further keyword arguments are passed to the writer. See [help\(\)](#) to see what arguments are available for a particular format.

imageio.mvolwrite

`imageio.mvolwrite(uri, vols, format=None, **kwargs)`

Write multiple volumes to the specified file.

Parameters

- uri** [{str, pathlib.Path, file}] The resource to write the volumes to, e.g. a filename, pathlib.Path or file object, see the docs for more info.
- ims** [sequence of numpy arrays] The image data. Each array must be NxMxL (or NxMxLxK if each voxel is a tuple).
- format** [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.
- kwargs** [...] Further keyword arguments are passed to the writer. See [help\(\)](#) to see what arguments are available for a particular format.

More control

For a larger degree of control, imageio provides functions [get_reader\(\)](#) and [get_writer\(\)](#). They respectively return an [Reader](#) and an [Writer](#) object, which can be used to read/write data and meta data in a more controlled manner. This also allows specific scientific formats to be exposed in a way that best suits that file-format.

`imageio.get_reader(uri, format=None, mode='?', **kwargs)`

Returns a [Reader](#) object which can be used to read data and meta data from the specified file.

Parameters

- uri** [{str, pathlib.Path, bytes, file}] The resource to load the image from, e.g. a filename, pathlib.Path, http address or file object, see the docs for more info.
- format** [str] The format to use to read the file. By default imageio selects the appropriate for you based on the filename and its contents.
- mode** [{ 'i', 'I', 'v', 'V', '?' }] Used to give the reader a hint on what the user expects (default "?"): "i" for an image, "I" for multiple images, "v" for a volume, "V" for multiple volumes, "?" for don't care.
- kwargs** [...] Further keyword arguments are passed to the reader. See [help\(\)](#) to see what arguments are available for a particular format.

`imageio.get_writer(uri, format=None, mode='?', **kwargs)`

Returns a [Writer](#) object which can be used to write data and meta data to the specified file.

Parameters

- uri** [{str, pathlib.Path, file}] The resource to write the image to, e.g. a filename, pathlib.Path or file object, see the docs for more info.
- format** [str] The format to use to write the file. By default imageio selects the appropriate for you based on the filename.
- mode** [{ 'i', 'I', 'v', 'V', '?' }] Used to give the writer a hint on what the user expects (default "?"): "i" for an image, "I" for multiple images, "v" for a volume, "V" for multiple volumes, "?" for don't care.

kwargs [...] Further keyword arguments are passed to the writer. See [help\(\)](#) to see what arguments are available for a particular format.

class `imageio.core.format.Reader(format, request)`

The purpose of a reader object is to read data from an image resource, and should be obtained by calling [get_reader\(\)](#).

A reader can be used as an iterator to read multiple images, and (if the format permits) only reads data from the file when new data is requested (i.e. streaming). A reader can also be used as a context manager so that it is automatically closed.

Plugins implement Reader's for different formats. Though rare, plugins may provide additional functionality (beyond what is provided by the base reader class).

Attributes

closed Whether the reader/writer is closed.

format The *Format* object corresponding to the current read/write operation.

request The *Request* object corresponding to the current read/write operation.

`close()`

Flush and close the reader/writer. This method has no effect if it is already closed.

property `closed`

Whether the reader/writer is closed.

property `format`

The *Format* object corresponding to the current read/write operation.

`get_data(index, **kwargs)`

Read image data from the file, using the image index. The returned image has a 'meta' attribute with the meta data. Raises `IndexError` if the index is out of range.

Some formats may support additional keyword arguments. These are listed in the documentation of those formats.

`get_length()`

Get the number of images in the file. (Note: you can also use `len(reader_object)`.)

The result can be:

- 0 for files that only have meta data
- 1 for singleton images (e.g. in PNG, JPEG, etc.)
- N for image series
- inf for streams (series of unknown length)

`get_meta_data(index=None)`

Read meta data from the file. using the image index. If the index is omitted or `None`, return the file's (global) meta data.

Note that `get_data` also provides the meta data for the returned image as an attribute of that image.

The meta data is a dict, which shape depends on the format. E.g. for JPEG, the dict maps group names to subdicts and each group is a dict with name-value pairs. The groups represent the different metadata formats (EXIF, XMP, etc.).

get_next_data(kwargs)**

Read the next image from the series.

Some formats may support additional keyword arguments. These are listed in the documentation of those formats.

iter_data()

Iterate over all images in the series. (Note: you can also iterate over the reader object.)

property request

The *Request* object corresponding to the current read/write operation.

set_image_index(index)

Set the internal pointer such that the next call to `get_next_data()` returns the image specified by the index

class imageio.core.format.Writer(format, request)

The purpose of a writer object is to write data to an image resource, and should be obtained by calling `get_writer()`.

A writer will (if the format permits) write data to the file as soon as new data is provided (i.e. streaming). A writer can also be used as a context manager so that it is automatically closed.

Plugins implement Writer's for different formats. Though rare, plugins may provide additional functionality (beyond what is provided by the base writer class).

Attributes

closed Whether the reader/writer is closed.

format The *Format* object corresponding to the current read/write operation.

request The *Request* object corresponding to the current read/write operation.

append_data(im, meta={})

Append an image (and meta data) to the file. The final meta data that is used consists of the meta data on the given image (if applicable), updated with the given meta data.

close()

Flush and close the reader/writer. This method has no effect if it is already closed.

property closed

Whether the reader/writer is closed.

property format

The *Format* object corresponding to the current read/write operation.

property request

The *Request* object corresponding to the current read/write operation.

set_meta_data(meta)

Sets the file's (global) meta data. The meta data is a dict which shape depends on the format. E.g. for JPEG the dict maps group names to subdicts, and each group is a dict with name-value pairs. The groups represents the different metadata formats (EXIF, XMP, etc.).

Note that some meta formats may not be supported for writing, and individual fields may be ignored without warning if they are invalid.

3.2 Plugins & Backend Libraries (Advanced Usage)

Sometimes, you need to do more than just “load an image, done”. Sometimes you need to use a very specific feature of a very specific backend. ImageIOs allows you to do so by allowing its plugins to extend the core API. Typically this is done in the form of additional keyword arguments (`kwargs`). Below you can find a list of available plugins and which arguments they support.

<code>imageio.plugins.bsdf</code>	Read/Write BSDF files.
<code>imageio.plugins.dicom</code>	Read DICOM files.
<code>imageio.plugins.feisem</code>	Read TIFF from FEI SEM microscopes.
<code>imageio.plugins.ffmpeg</code>	Read/Write video using FFMPEG
<code>imageio.plugins.fits</code>	Read FITS files.
<code>imageio.plugins.freeimage</code>	Read/Write images using FreeImage.
<code>imageio.plugins.gdal</code>	Read GDAL files.
<code>imageio.plugins.lytro</code>	Read LFR files (Lytro Illum).
<code>imageio.plugins.npz</code>	Read/Write NPZ files.
<code>imageio.plugins.pillow</code>	Read/Write images using Pillow/PIL.
<code>imageio.plugins.pillow_legacy</code>	Read/Write images using pillow/PIL (legacy).
<code>imageio.plugins.simpleitk</code>	Read/Write images using SimpleITK.
<code>imageio.plugins.spe</code>	Read SPE files.
<code>imageio.plugins.swf</code>	Read/Write SWF files.
<code>imageio.plugins.tiffio</code>	Read/Write TIFF files.

3.2.1 imageio.plugins.bsdf

Read/Write BSDF files.

Backend Library: internal

The BSDF format enables reading and writing of image data in the BSDF serialization format. This format allows storage of images, volumes, and series thereof. Data can be of any numeric data type, and can optionally be compressed. Each image/volume can have associated meta data, which can consist of any data type supported by BSDF.

By default, image data is lazily loaded; the actual image data is not read until it is requested. This allows storing multiple images in a single file and still have fast access to individual images. Alternatively, a series of images can be read in streaming mode, reading images as they are read (e.g. from http).

BSDF is a simple generic binary format. It is easy to extend and there are standard extension definitions for 2D and 3D image data. Read more at <http://bsdf.io>.

Parameters

random_access [bool] Whether individual images in the file can be read in random order. Defaults to True for normal files, and to False when reading from HTTP. If False, the file is read in “streaming mode”, allowing reading files as they are read, but without support for “rewinding”. Note that setting this to True when reading from HTTP, the whole file is read upon opening it (since lazy loading is not possible over HTTP).

compression [int] Use 0 or “no” for no compression, 1 or “zlib” for Zlib compression (same as zip files and PNG), and 2 or “bz2” for Bz2 compression (more compact but slower). Default 1 (zlib). Note that some BSDF implementations may not support compression (e.g. JavaScript).

3.2.2 imageio.plugins.dicom

Read DICOM files.

Backend Library: internal

A format for reading DICOM images: a common format used to store medical image data, such as X-ray, CT and MRI.

This format borrows some code (and ideas) from the pydicom project. However, only a predefined subset of tags are extracted from the file. This allows for great simplifications allowing us to make a stand-alone reader, and also results in a much faster read time.

By default, only uncompressed and deflated transfer syntaxes are supported. If `gdcm` or `dcmk` is installed, these will be used to automatically convert the data. See <https://github.com/malaterre/GDCM/releases> for installing GDCM.

This format provides functionality to group images of the same series together, thus extracting volumes (and multiple volumes). Using `volread` will attempt to yield a volume. If multiple volumes are present, the first one is given. Using `mimread` will simply yield all images in the given directory (not taking series into account).

Parameters

progress [{True, False, BaseProgressIndicator}] Whether to show progress when reading from multiple files. Default True. By passing an object that inherits from `BaseProgressIndicator`, the way in which progress is reported can be customized.

3.2.3 imageio.plugins.feisem

Read TIFF from FEI SEM microscopes.

Backend Library: internal

This format is based on [TIFF](#), and supports the same parameters. FEI microscopes append metadata as ASCII text at the end of the file, which this reader correctly extracts.

Parameters

discard_watermark [bool] If True (default), discard the bottom rows of the image, which contain no image data, only a watermark with metadata.

watermark_height [int] The height in pixels of the FEI watermark. The default is 70.

See Also

`imageio.plugins.tiff`

3.2.4 imageio.plugins.ffmpeg

Read/Write video using FFMPEG

Backend Library: <https://github.com/imageio/imageio-ffmpeg>

Note: To use this plugin you have to install its backend:

```
pip install imageio[ffmpeg]
```

The ffmpeg format provides reading and writing for a wide range of movie formats such as .avi, .mpeg, .mp4, etc. as well as the ability to read streams from webcams and USB cameras. It is based on ffmpeg and is inspired by/based on [moviepy](#) by Zulko.

Parameters for reading

fps [scalar] The number of frames per second to read the data at. Default None (i.e. read at the file's own fps). One can use this for files with a variable fps, or in cases where imageio is unable to correctly detect the fps. In case of trouble opening camera streams, it may help to set an explicit fps value matching a framerate supported by the camera.

loop [bool] If True, the video will rewind as soon as a frame is requested beyond the last frame. Otherwise, IndexError is raised. Default False. Setting this to True will internally call `count_frames()`, and set the reader's length to that value instead of inf.

size [str | tuple] The frame size (i.e. resolution) to read the images, e.g. (100, 100) or "640x480". For camera streams, this allows setting the capture resolution. For normal video data, ffmpeg will rescale the data.

dtype [str | type] The dtype for the output arrays. Determines the bit-depth that is requested from ffmpeg. Supported dtypes: uint8, uint16. Default: uint8.

pixelformat [str] The pixel format for the camera to use (e.g. "yuyv422" or "gray"). The camera needs to support the format in order for this to take effect. Note that the images produced by this reader are always RGB.

input_params [list] List additional arguments to ffmpeg for input file options. (Can also be provided as `ffmpeg_params` for backwards compatibility) Example ffmpeg arguments to use aggressive error handling: ['-err_detect', 'aggressive']

output_params [list] List additional arguments to ffmpeg for output file options (i.e. the stream being read by imageio).

print_info [bool] Print information about the video file as reported by ffmpeg.

Parameters for writing

fps [scalar] The number of frames per second. Default 10.

codec [str] the video codec to use. Default 'libx264', which represents the widely available mpeg4. Except when saving .wmv files, then the defaults is 'msmpeg4' which is more commonly supported for windows

quality [float | None] Video output quality. Default is 5. Uses variable bit rate. Highest quality is 10, lowest is 0. Set to None to prevent variable bitrate flags to FFMPEG so you can manually specify them using `output_params` instead. Specifying a fixed bitrate using 'bitrate' disables this parameter.

bitrate [int | None] Set a constant bitrate for the video encoding. Default is None causing 'quality' parameter to be used instead. Better quality videos with smaller file sizes will result from using the 'quality' variable bitrate parameter rather than specifying a fixed bitrate with this parameter.

pixelformat: **str** The output video pixel format. Default is ‘yuv420p’ which most widely supported by video players.

input_params [list] List additional arguments to ffmpeg for input file options (i.e. the stream that imageio provides).

output_params [list] List additional arguments to ffmpeg for output file options. (Can also be provided as `ffmpeg_params` for backwards compatibility) Example ffmpeg arguments to use only intra frames and set aspect ratio: [‘-intra’, ‘-aspect’, ‘16:9’]

ffmpeg_log_level: **str** Sets ffmpeg output log level. Default is “warning”. Values can be “quiet”, “panic”, “fatal”, “error”, “warning”, “info”, “verbose”, or “debug”. Also prints the FFMPEG command being used by imageio if “info”, “verbose”, or “debug”.

macro_block_size: **int** Size constraint for video. Width and height, must be divisible by this number. If not divisible by this number imageio will tell ffmpeg to scale the image up to the next closest size divisible by this number. Most codecs are compatible with a macroblock size of 16 (default), some can go smaller (4, 8). To disable this automatic feature set it to None or 1, however be warned many players can’t decode videos that are odd in size and some codecs will produce poor results or fail. See <https://en.wikipedia.org/wiki/Macroblock>.

Notes

If you are using anaconda and `anaconda/ffmpeg` you will not be able to encode/decode H.264 (likely due to licensing concerns). If you need this format on anaconda install `conda-forge/ffmpeg` instead.

You can use the `IMAGEIO_FFMPEG_EXE` environment variable to force using a specific ffmpeg executable.

To get the number of frames before having read them all, you can use the `reader.count_frames()` method (the reader will then use `imageio_ffmpeg.count_frames_and_secs()` to get the exact number of frames, note that this operation can take a few seconds on large files). Alternatively, the number of frames can be estimated from the fps and duration in the meta data (though these values themselves are not always present/reliable).

3.2.5 imageio.plugins.fits

Read FITS files.

Backend Library: [Astropy](#)

Note: To use this plugin you have to install its backend:

```
pip install imageio[fits]
```

Flexible Image Transport System (FITS) is an open standard defining a digital file format useful for storage, transmission and processing of scientific and other images. FITS is the most commonly used digital file format in astronomy.

Parameters

cache [bool] If the file name is a URL, `~astropy.utils.data.download_file` is used to open the file. This specifies whether or not to save the file locally in Astropy’s download cache (default: `True`).

uint [bool] Interpret signed integer data where `BZERO` is the central value and `BSCALE == 1` as unsigned integer data. For example, `int16` data with `BZERO = 32768` and `BSCALE = 1` would be treated as `uint16` data.

Note, for backward compatibility, the kwarg `uint16` may be used instead. The kwarg was renamed when support was added for integers of any size.

ignore_missing_end [bool] Do not issue an exception when opening a file that is missing an END card in the last header.

checksum [bool or str] If *True*, verifies that both DATASUM and CHECKSUM card values (when present in the HDU header) match the header and data of all HDU's in the file. Updates to a file that already has a checksum will preserve and update the existing checksums unless this argument is given a value of 'remove', in which case the CHECKSUM and DATASUM values are not checked, and are removed when saving changes to the file.

disable_image_compression [bool, optional] If *True*, treats compressed image HDU's like normal binary table HDU's.

do_not_scale_image_data [bool] If *True*, image data is not scaled using BSCALE/BZERO values when read.

ignore_blank [bool] If *True*, the BLANK keyword is ignored if present.

scale_back [bool] If *True*, when saving changes to a file that contained scaled image data, restore the data to the original type and reapply the original BSCALE/BZERO values. This could lead to loss of accuracy if scaling back to integer values after performing floating point operations on the data.

3.2.6 imageio.plugins.freeimage

Read/Write images using FreeImage.

Backend Library: [FreeImage](#)

Note: To use this plugin you have to install its backend:

```
imageio_download_bin freeimage
```

or you can download the backend using the function:

```
imageio.plugins.freeimage.download()
```

Each Freeimage format has the `flags` keyword argument. See the [Freeimage documentation](#) for more information.

Parameters

flags [int] A freeimage-specific option. In most cases we provide explicit parameters for influencing image reading.

3.2.7 imageio.plugins.gdal

Read GDAL files.

Backend: [GDAL](#)

Note: To use this plugin you have to install its backend:

```
pip install imageio[gdal]
```


Parameters

none

3.2.8 imageio.plugins.lytro

Read LFR files (Lytro Illum).

Backend: internal

Plugin to read Lytro Illum .lfr and .raw files as produced by the Lytro Illum light field camera. It is actually a collection of plugins, each supporting slightly different keyword arguments

Parameters

meta_only [bool] Whether to only read the metadata.

include_thumbnail [bool] (only for lytro-lfr and lytro-lfp) Whether to include an image thumbnail in the metadata.

3.2.9 imageio.plugins.npz

Read/Write NPZ files.

Backend: [Numpy](#)

NPZ is a file format by numpy that provides storage of array data using gzip compression. This imageio plugin supports data of any shape, and also supports multiple images per file. However, the npz format does not provide streaming; all data is read/written at once. Further, there is no support for meta data.

See the BSDF format for a similar (but more fully featured) format.

Parameters

None

Notes

This format is not available on Pypy.

3.2.10 imageio.plugins.pillow

Read/Write images using Pillow/PIL.

Backend Library: [Pillow](#)

Plugin that wraps the the Pillow library. Pillow is a friendly fork of PIL (Python Image Library) and supports reading and writing of common formats (jpg, png, gif, tiff, ...). For the complete list of features and supported formats please refer to pillows official docs (see the Backend Library link).

Parameters

request [Request] A request object representing the resource to be operated on.

Methods

<code>PillowPlugin.read(*[, index, mode, rotate, ...])</code>	Parses the given URI and creates a ndarray from it.
<code>PillowPlugin.write(image, *[, mode, format])</code>	Write an ndimage to the URI specified in path.
<code>PillowPlugin.iter(*[, mode, rotate, apply_gamma])</code>	Iterate over all ndimages/frames in the URI
<code>PillowPlugin.get_meta(*[, index])</code>	

imageio.plugins.pillow.PillowPlugin.read

`PillowPlugin.read(*, index=0, mode=None, rotate=False, apply_gamma=False) → numpy.ndarray`
Parses the given URI and creates a ndarray from it.

Parameters

index [{integer}] If the URI contains a list of ndimages (multiple frames) return the index-th image/frame. If None, read all ndimages (frames) in the URI and attempt to stack them along a new 0-th axis (equivalent to `np.stack(imgs, axis=0)`)

mode [{str, None}] Convert the image to the given mode before returning it. If None, the mode will be left unchanged. Possible modes can be found at: <https://pillow.readthedocs.io/en/stable/handbook/concepts.html#modes>

rotate [{bool}] If set to True and the image contains an EXIF orientation tag, apply the orientation before returning the ndimage.

apply_gamma [{bool}] If True and the image contains metadata about gamma, apply gamma correction to the image.

Returns

ndimage [ndarray] A numpy array containing the loaded image data

Notes

If you open a GIF - or any other format using color pallets - you may wish to manually set the *mode* parameter. Otherwise, the numbers in the returned image will refer to the entries in the color pallet, which is discarded during conversion to ndarray.

imageio.plugins.pillow.PillowPlugin.write

`PillowPlugin.write(image: numpy.ndarray, *, mode=None, format=None, **kwargs) → Optional[bytes]`
Write an ndimage to the URI specified in path.

If the URI points to a file on the current host and the file does not yet exist it will be created. If the file exists already, it will be appended if possible; otherwise, it will be replaced.

If necessary, the image is broken down along the leading dimension to fit into individual frames of the chosen format. If the format doesn't support multiple frames, and `IOError` is raised.

Parameters

- image** [ndarray] The ndimage to write.
- mode** [{str, None}] Specify the image's color format. If None (default), the mode is inferred from the array's shape and dtype. Possible modes can be found at: <https://pillow.readthedocs.io/en/stable/handbook/concepts.html#modes>
- format** [{str, None}] Optional format override. If omitted, the format to use is determined from the filename extension. If a file object was used instead of a filename, this parameter must always be used.
- kwargs** [...] Extra arguments to pass to pillow. If a writer doesn't recognise an option, it is silently ignored. The available options are described in pillow's [image format documentation](#) for each writer.

Notes

When writing batches of very narrow (2-4 pixels wide) gray images set the mode explicitly to avoid the batch being identified as a colored image.

imageio.plugins.pillow.PillowPlugin.iter

PillowPlugin.**iter**(*, mode=None, rotate=False, apply_gamma=False) → numpy.ndarray
Iterate over all ndimages/frames in the URI

Parameters

- mode** [{str, None}] Convert the image to the given mode before returning it. If None, the mode will be left unchanged. Possible modes can be found at: <https://pillow.readthedocs.io/en/stable/handbook/concepts.html#modes>
- rotate** [{bool}] If set to True and the image contains an EXIF orientation tag, apply the orientation before returning the ndimage.
- apply_gamma** [{bool}] If True and the image contains metadata about gamma, apply gamma correction to the image.

imageio.plugins.pillow.PillowPlugin.get_meta

PillowPlugin.**get_meta**(*, index=0) → Dict[str, Any]

3.2.11 imageio.plugins.pillow_legacy

Read/Write images using pillow/PIL (legacy).

Backend Library: [Pillow](#)

Pillow is a friendly fork of PIL (Python Image Library) and supports reading and writing of common formats (jpg, png, gif, tiff, ...). While these docs provide an overview of some of its features, pillow is constantly improving. Hence, the complete list of features can be found in pillow's official docs (see the Backend Library link).

Parameters for Reading

pilmode [str] (Available for all formats except GIF-PIL) From the Pillow documentation:

- ‘L’ (8-bit pixels, grayscale)
- ‘P’ (8-bit pixels, mapped to any other mode using a color palette)
- ‘RGB’ (3x8-bit pixels, true color)
- ‘RGBA’ (4x8-bit pixels, true color with transparency mask)
- ‘CMYK’ (4x8-bit pixels, color separation)
- ‘YCbCr’ (3x8-bit pixels, color video format)
- ‘I’ (32-bit signed integer pixels)
- ‘F’ (32-bit floating point pixels)

PIL also provides limited support for a few special modes, including ‘LA’ (‘L’ with alpha), ‘RGBX’ (true color with padding) and ‘RGBa’ (true color with premultiplied alpha).

When translating a color image to grayscale (mode ‘L’, ‘I’ or ‘F’), the library uses the ITU-R 601-2 luma transform:

$$L = R * 299/1000 + G * 587/1000 + B * 114/1000$$

as_gray [bool] (Available for all formats except GIF-PIL) If True, the image is converted using mode ‘F’. When *mode* is not None and *as_gray* is True, the image is first converted according to *mode*, and the result is then “flattened” using mode ‘F’.

ignoregamma [bool] (Only available in PNG-PIL) Avoid gamma correction. Default True.

exifrotate [bool] (Only available in JPEG-PIL) Automatically rotate the image according to exif flag. Default True.

Parameters for saving

optimize [bool] (Only available in PNG-PIL) If present and true, instructs the PNG writer to make the output file as small as possible. This includes extra processing in order to find optimal encoder settings.

transparency: (Only available in PNG-PIL) This option controls what color image to mark as transparent.

dpi: tuple of two scalars (Only available in PNG-PIL) The desired dpi in each direction.

pnginfo: PIL.PngImagePlugin.PngInfo (Only available in PNG-PIL) Object containing text tags.

compress_level: int (Only available in PNG-PIL) ZLIB compression level, a number between 0 and 9: 1 gives best speed, 9 gives best compression, 0 gives no compression at all. Default is 9. When **optimize** option is True **compress_level** has no effect (it is set to 9 regardless of a value passed).

compression: int (Only available in PNG-PIL) Compatibility with the freeimage PNG format. If given, it overrides **compress_level**.

icc_profile: (Only available in PNG-PIL) The ICC Profile to include in the saved file.

bits (experimental): int (Only available in PNG-PIL) This option controls how many bits to store. If omitted, the PNG writer uses 8 bits (256 colors).

quantize: (Only available in PNG-PIL) Compatibility with the freeimage PNG format. If given, it overrides bits. In this case, given as a number between 1-256.

dictionary (experimental): dict (Only available in PNG-PIL) Set the ZLIB encoder dictionary.

- prefer_uint8: bool** (Only available in PNG-PIL) Let the PNG writer truncate uint16 image arrays to uint8 if their values fall within the range [0, 255]. Defaults to true for legacy compatibility, however it is recommended to set this to false to avoid unexpected behavior when saving e.g. weakly saturated images.
- quality** [scalar] (Only available in JPEG-PIL) The compression factor of the saved image (1..100), higher numbers result in higher quality but larger file size. Default 75.
- progressive** [bool] (Only available in JPEG-PIL) Save as a progressive JPEG file (e.g. for images on the web). Default False.
- optimize** [bool] (Only available in JPEG-PIL) On saving, compute optimal Huffman coding tables (can reduce a few percent of file size). Default False.
- dpi** [tuple of int] (Only available in JPEG-PIL) The pixel density, (x,y).
- icc_profile** [object] (Only available in JPEG-PIL) If present and true, the image is stored with the provided ICC profile. If this parameter is not provided, the image will be saved with no profile attached.
- exif** [dict] (Only available in JPEG-PIL) If present, the image will be stored with the provided raw EXIF data.
- subsampling** [str] (Only available in JPEG-PIL) Sets the subsampling for the encoder. See Pillow docs for details.
- qttables** [object] (Only available in JPEG-PIL) Set the qttables for the encoder. See Pillow docs for details.
- quality_mode** [str] (Only available in JPEG2000-PIL) Either “*rates*” or “*dB*” depending on the units you want to use to specify image quality.
- quality** [float] (Only available in JPEG2000-PIL) Approximate size reduction (if quality mode is *rates*) or a signal to noise ratio in decibels (if quality mode is *dB*).
- loop** [int] (Only available in GIF-PIL) The number of iterations. Default 0 (meaning loop indefinitely).
- duration** [{float, list}] (Only available in GIF-PIL) The duration (in seconds) of each frame. Either specify one value that is used for all frames, or one value for each frame. Note that in the GIF format the duration/delay is expressed in hundredths of a second, which limits the precision of the duration.
- fps** [float] (Only available in GIF-PIL) The number of frames per second. If duration is not given, the duration for each frame is set to 1/fps. Default 10.
- palettesize** [int] (Only available in GIF-PIL) The number of colors to quantize the image to. Is rounded to the nearest power of two. Default 256.
- subrectangles** [bool] (Only available in GIF-PIL) If True, will try and optimize the GIF by storing only the rectangular parts of each frame that change with respect to the previous. Default False.

Notes

To enable JPEG 2000 support, you need to build and install the OpenJPEG library, version 2.0.0 or higher, before building the Python Imaging Library. Windows users can install the OpenJPEG binaries available on the OpenJPEG website, but must add them to their PATH in order to use PIL (if you fail to do this, you will get errors about not being able to load the `_imaging` DLL).

GIF images read with this plugin are always RGBA. The alpha channel is ignored when saving RGB images.

3.2.12 imageio.plugins.simpleitk

Read/Write images using SimpleITK.

Backend: [Insight Toolkit](#)

Note: To use this plugin you have to install its backend:

```
pip install imageio[itk]
```

The ItkFormat uses the ITK or SimpleITK library to support a range of ITK-related formats. It also supports a few common formats (e.g. PNG and JPEG).

Parameters

None

3.2.13 imageio.plugins.spe

Read SPE files.

Backend: internal

This plugin supports reading files saved in the Princeton Instruments SPE file format.

Parameters for reading

char_encoding [str] Character encoding used to decode strings in the metadata. Defaults to “latin1”.

check_filesize [bool] The number of frames in the file is stored in the file header. However, this number may be wrong for certain software. If this is *True* (default), derive the number of frames also from the file size and raise a warning if the two values do not match.

sdt_meta [bool] If set to *True* (default), check for special metadata written by the *SdT-control* software. Does not have an effect for files written by other software.

Metadata for reading

ROIs [list of dict] Regions of interest used for recording images. Each dict has the “top_left” key containing x and y coordinates of the top left corner, the “bottom_right” key with x and y coordinates of the bottom right corner, and the “bin” key with number of binned pixels in x and y directions.

comments [list of str] The SPE format allows for 5 comment strings of 80 characters each.

controller_version [int] Hardware version

logic_output [int] Definition of output BNC

amp_hi_cap_low_noise [int] Amp switching mode

mode [int] Timing mode

exp_sec [float] Alternative exposure in seconds

date [str] Date string

detector_temp [float] Detector temperature

detector_type [int] CCD / diode array type

st_diode [int] Trigger diode

delay_time [float] Used with async mode

shutter_control [int] Normal, disabled open, or disabled closed

absorb_live [bool] on / off

absorb_mode [int] Reference strip or file

can_do_virtual_chip [bool] True or False whether chip can do virtual chip

threshold_min_live [bool] on / off

threshold_min_val [float] Threshold minimum value

threshold_max_live [bool] on / off

threshold_max_val [float] Threshold maximum value

time_local [str] Experiment local time

time_utc [str] Experiment UTC time

adc_offset [int] ADC offset

adc_rate [int] ADC rate

adc_type [int] ADC type

adc_resolution [int] ADC resolution

adc_bit_adjust [int] ADC bit adjust

gain [int] gain

sw_version [str] Version of software which created this file

spare_4 [bytes] Reserved space

readout_time [float] Experiment readout time

type [str] Controller type

clockspeed_us [float] Vertical clock speed in microseconds

readout_mode [[“full frame”, “frame transfer”, “kinetics”, “”]] Readout mode. Empty string means that this was not set by the Software.

window_size [int] Window size for Kinetics mode

file_header_ver [float] File header version

chip_size [[int, int]] x and y dimensions of the camera chip

virt_chip_size [[int, int]] Virtual chip x and y dimensions

pre_pixels [[int, int]] Pre pixels in x and y dimensions

post_pixels [[int, int],] Post pixels in x and y dimensions

geometric [list of {“rotate”, “reverse”, “flip”}] Geometric operations

sdt_major_version [int] (only for files created by SDT-control) Major version of SDT-control software

sdt_minor_version [int] (only for files created by SDT-control) Minor version of SDT-control software

sdt_controller_name [str] (only for files created by SDT-control) Controller name

exposure_time [float] (only for files created by SDT-control) Exposure time in seconds

color_code [str] (only for files created by SDT-control) Color channels used

detection_channels [int] (only for files created by SDT-control) Number of channels

background_subtraction [bool] (only for files created by SDT-control) Whether background subtraction was turned on

em_active [bool] (only for files created by SDT-control) Whether EM was turned on

em_gain [int] (only for files created by SDT-control) EM gain

modulation_active [bool] (only for files created by SDT-control) Whether laser modulation (“attenuate”) was turned on

pixel_size [float] (only for files created by SDT-control) Camera pixel size

sequence_type [str] (only for files created by SDT-control) Type of sequence (standard, TOCCSL, arbitrary, ...)

grid [float] (only for files created by SDT-control) Sequence time unit (“grid size”) in seconds

n_macro [int] (only for files created by SDT-control) Number of macro loops

delay_macro [float] (only for files created by SDT-control) Time between macro loops in seconds

n_mini [int] (only for files created by SDT-control) Number of mini loops

delay_mini [float] (only for files created by SDT-control) Time between mini loops in seconds

n_micro [int] (only for files created by SDT-control) Number of micro loops

delay_micro [float] (only for files created by SDT-control) Time between micro loops in seconds

n_subpics [int] (only for files created by SDT-control) Number of sub-pictures

delay_shutter [float] (only for files created by SDT-control) Camera shutter delay in seconds

delay_prebleach [float] (only for files created by SDT-control) Pre-bleach delay in seconds

bleach_time [float] (only for files created by SDT-control) Bleaching time in seconds

recovery_time [float] (only for files created by SDT-control) Recovery time in seconds

comment [str] (only for files created by SDT-control) User-entered comment. This replaces the “comments” field.

datetime [datetime.datetime] (only for files created by SDT-control) Combines the “date” and “time_local” keys. The latter two plus “time_utc” are removed.

modulation_script [str] (only for files created by SDT-control) Laser modulation script. Replaces the “spare_4” key.

3.2.14 imageio.plugins.swf

Read/Write SWF files.

Backend: internal

Shockwave flash (SWF) is a media format designed for rich and interactive animations. This plugin makes use of this format to store a series of images in a lossless format with good compression (zlib). The resulting images can be shown as an animation using a flash player (such as the browser).

SWF stores images in RGBA format. RGB or grayscale images are automatically converted. SWF does not support meta data.

Parameters for reading

loop [bool] If True, the video will rewind as soon as a frame is requested beyond the last frame. Otherwise, `IndexError` is raised. Default False.

Parameters for saving

fps [int] The speed to play the animation. Default 12.

loop [bool] If True, add a tag to the end of the file to play again from the first frame. Most flash players will then play the movie in a loop. Note that the imageio SWF Reader does not check this tag. Default True.

html [bool] If the output is a file on the file system, write an html file (in HTML5) that shows the animation. Default False.

compress [bool] Whether to compress the swf file. Default False. You probably don't want to use this. This does not decrease the file size since the images are already compressed. It will result in slower read and write time. The only purpose of this feature is to create compressed SWF files, so that we can test the functionality to read them.

3.2.15 imageio.plugins.tifffile

Read/Write TIFF files.

Backend: internal

Provides support for a wide range of Tiff images using the tifffile backend.

Parameters for reading

offset [int] Optional start position of embedded file. By default this is the current file position.

size [int] Optional size of embedded file. By default this is the number of bytes from the 'offset' to the end of the file.

multifile [bool] If True (default), series may include pages from multiple files. Currently applies to OME-TIFF only.

multifile_close [bool] If True (default), keep the handles of other files in multifile series closed. This is inefficient when few files refer to many pages. If False, the C runtime may run out of resources.

Parameters for saving

bigtiff [bool] If True, the BigTIFF format is used.

byteorder [{ '<', '>' }] The endianness of the data in the file. By default this is the system's native byte order.

software [str] Name of the software used to create the image. Saved with the first page only.

Metadata for reading

planar_configuration [{ 'contig', 'planar' }] Specifies if samples are stored contiguous or in separate planes. By default this setting is inferred from the data shape. 'contig': last dimension contains samples. 'planar': third last dimension contains samples.

resolution_unit [int] The resolution unit stored in the TIFF tag. Usually 1 means no/unknown unit, 2 means dpi (inch), 3 means dpc (centimeter).

resolution [(float, float, str)] A tuple formatted as (X_resolution, Y_resolution, unit). The unit is a string representing one of the following units:

NONE	# <i>No unit or unit unknown</i>
INCH	# <i>dpi</i>
CENTIMETER	# <i>cpi</i>
MILLIMETER	
MICROMETER	

compression [int] Value indicating the compression algorithm used, e.g. 5 is LZW, 7 is JPEG, 8 is deflate. If 1, data are uncompressed.

predictor [int] Value 2 indicates horizontal differencing was used before compression, while 3 indicates floating point horizontal differencing. If 1, no prediction scheme was used before compression.

orientation [{ 'top_left', 'bottom_right', ... }] Oriented of image array.

is_rgb [bool] True if page contains a RGB image.

is_contig [bool] True if page contains a contiguous image.

is_tiled [bool] True if page contains tiled image.

is_palette [bool] True if page contains a palette-colored image and not OME or STK.

is_reduced [bool] True if page is a reduced image of another image.

is_shaped [bool] True if page contains shape in image_description tag.

is_fluoview [bool] True if page contains FluoView MM_STAMP tag.

is_nih [bool] True if page contains NIH image header.

is_micromanager [bool] True if page contains Micro-Manager metadata.

is_ome [bool] True if page contains OME-XML in image_description tag.

is_sgi [bool] True if page contains SGI image and tile depth tags.

is_mdgel [bool] True if page contains md_file_tag tag.

is_mediacy [bool] True if page contains Media Cybernetics Id tag.

is_stk [bool] True if page contains UIC2Tag tag.

is_lsm [bool] True if page contains LSM CZ_LSM_INFO tag.

description [str] Image description

description1 [str] Additional description

is_imagej [None or str] ImageJ metadata

software [str] Software used to create the TIFF file

datetime [datetime.datetime] Creation date and time

Metadata for writing

photometric [{ 'minisblack', 'miniswhite', 'rgb' }] The color space of the image data. By default this setting is inferred from the data shape.

planarconfig [{ 'contig', 'planar' }] Specifies if samples are stored contiguous or in separate planes. By default this setting is inferred from the data shape. 'contig': last dimension contains samples. 'planar': third last dimension contains samples.

resolution [(float, float) or ((int, int), (int, int))] X and Y resolution in dots per inch as float or rational numbers.

description [str] The subject of the image. Saved with the first page only.

compress [int] Values from 0 to 9 controlling the level of zlib (deflate) compression. If 0, data are written uncompressed (default).

predictor [bool] If True, horizontal differencing is applied before compression. Note that using an int literal 1 actually means no prediction scheme will be used.

volume [bool] If True, volume data are stored in one tile (if applicable) using the SGI image_depth and tile_depth tags. Image width and depth must be multiple of 16. Few software can read this format, e.g. MeVisLab.

writeshape [bool] If True, write the data shape to the image_description tag if necessary and no other description is given.

extratags: sequence of tuples Additional tags as [(code, dtype, count, value, writeonce)].

code [int] The TIFF tag Id.

dtype [str] Data type of items in 'value' in Python struct format. One of B, s, H, I, 2I, b, h, i, f, d, Q, or q.

count [int] Number of data values. Not used for string values.

value [sequence] 'Count' values compatible with 'dtype'.

writeonce [bool] If True, the tag is written to the first page only.

Notes

Global metadata is stored with the first frame in a TIFF file. Thus calling `Format.Writer.set_meta_data()` after the first frame was written has no effect. Also, global metadata is ignored if metadata is provided via the *meta* argument of `Format.Writer.append_data()`.

If you have installed tiffle as a Python package, imageio will attempt to use that as backend instead of the bundled backend. Doing so can provide access to new performance improvements and bug fixes.

4.1 The ImageIO Plugin API

Here you can find documentation on how to write your own plugin to allow ImageIO to access a new backend. Plugins are quite object oriented, and the relevant classes and their interaction are documented here:

<code>imageio.core.Format(name, description[, ...])</code>	Represents an implementation to read/write a particular file format
<code>imageio.core.Request(uri, mode, *[, format_hint])</code>	ImageResource handling utility.

4.1.1 imageio.core.Format

class `imageio.core.Format`(*name: str, description: str, extensions=None, modes: Optional[str] = None*)

Represents an implementation to read/write a particular file format

A format instance is responsible for 1) providing information about a format; 2) determining whether a certain file can be read/written with this format; 3) providing a reader/writer class.

Generally, imageio will select the right format and use that to read/write an image. A format can also be explicitly chosen in all read/write functions. Use `print(format)`, or `help(format_name)` to see its documentation.

To implement a specific format, one should create a subclass of `Format` and the `Format.Reader` and `Format.Writer` classes. See [imageio.plugins](#) for details.

Parameters

name [str] A short name of this format. Users can select a format using its name.

description [str] A one-line description of the format.

extensions [str | list | None] List of filename extensions that this format supports. If a string is passed it should be space or comma separated. The extensions are used in the documentation and to allow users to select a format by file extension. It is not used to determine what format to use for reading/saving a file.

modes [str] A string containing the modes that this format can handle ('iIvV'), "i" for an image, "I" for multiple images, "v" for a volume, "V" for multiple volumes. This attribute is used in the documentation and to select the formats when reading/saving a file.

Attributes

Reader

Writer

description A short description of this format.

doc The documentation for this format (name + description + docstring).

extensions A list of file extensions supported by this plugin.

modes A string specifying the modes that this format can handle.

name The name of this format.

Methods

<code>can_read(request)</code>	Get whether this format can read data from the specified uri.
<code>can_write(request)</code>	Get whether this format can write data to the specified uri.
<code>get_reader(request)</code>	Return a reader object that can be used to read data and info from the given file.
<code>get_writer(request)</code>	Return a writer object that can be used to write data and info to the given file.

Attribute and Method Details

Reader = None

Writer = None

description

A short description of this format.

doc

The documentation for this format (name + description + docstring).

extensions

A list of file extensions supported by this plugin. These are all lowercase with a leading dot.

modes

A string specifying the modes that this format can handle.

name

The name of this format.

can_read(request)

Get whether this format can read data from the specified uri.

can_write(request)

Get whether this format can write data to the specified uri.

get_reader(request)

Return a reader object that can be used to read data and info from the given file. Users are encouraged to use `imageio.get_reader()` instead.

get_writer(request)

Return a writer object that can be used to write data and info to the given file. Users are encouraged to use `imageio.get_writer()` instead.

4.1.2 imageio.core.Request

class imageio.core.Request(*uri, mode, *, format_hint: Optional[str] = None, **kwargs*)

ImageResource handling utility.

Represents a request for reading or saving an image resource. This object wraps information to that request and acts as an interface for the plugins to several resources; it allows the user to read from filenames, files, http, zip-files, raw bytes, etc., but offer a simple interface to the plugins via `get_file()` and `get_local_filename()`.

For each read/write operation a single Request instance is used and passed to the `can_read/can_write` method of a format, and subsequently to the Reader/Writer class. This allows rudimentary passing of information between different formats and between a format and associated reader/writer.

Parameters

uri [{str, bytes, file}] The resource to load the image from.

mode [str] The first character is “r” or “w”, indicating a read or write request. The second character is used to indicate the kind of data: “i” for an image, “I” for multiple images, “v” for a volume, “V” for multiple volumes, “?” for don’t care.

Attributes

extension The (lowercase) extension of the requested filename.

filename Name of the ImageResource.

firstbytes The first 256 bytes of the file.

format_hint

kwargs The dict of keyword arguments supplied by the user.

mode The mode of the request.

Methods

<code>finish()</code>	Wrap up this request.
<code>get_file()</code>	Get a file object for the resource associated with this request.
<code>get_local_filename()</code>	If the filename is an existing file on this filesystem, return that.
<code>get_result()</code>	For internal use.

Attribute and Method Details

extension

The (lowercase) extension of the requested filename. Suffixes in url’s are stripped. Can be None if the request is not based on a filename.

filename

Name of the ImageResource.

The uri for which reading/saving was requested. This can be a filename, an http address, or other resource identifier. Do not rely on the filename to obtain the data, but use `get_file()` or `get_local_filename()` instead.

firstbytes

The first 256 bytes of the file. These can be used to parse the header to determine the file-format.

format_hint

kwargs

The dict of keyword arguments supplied by the user.

mode

The mode of the request. The first character is “r” or “w”, indicating a read or write request. The second character is used to indicate the kind of data: “i” for an image, “I” for multiple images, “v” for a volume, “V” for multiple volumes, “?” for don’t care.

finish() → None

Wrap up this request.

Finishes any pending reads or writes, closes any open files and frees any resources allocated by this request.

get_file()

Get a file object for the resource associated with this request. If this is a reading request, the file is in read mode, otherwise in write mode. This method is not thread safe. Plugins should not close the file when done.

This is the preferred way to read/write the data. But if a format cannot handle file-like objects, they should use `get_local_filename()`.

get_local_filename()

If the filename is an existing file on this filesystem, return that. Otherwise a temporary file is created on the local file system which can be used by the format to read from or write to.

get_result()

For internal use. In some situations a write action can have a result (bytes data). That is obtained with this function.

Note: You can always check existing plugins if you want to see examples.

4.1.3 What methods to implement

To implement a new plugin, create a new class that inherits from `imageio.core.Format`. and implement the following functions:

<code>imageio.core.Format.__init__(name, description)</code>	Initialize the Plugin.
<code>imageio.core.Format._can_read(request)</code>	Check if Plugin can read from ImageResource.
<code>imageio.core.Format._can_write(request)</code>	Check if Plugin can write to ImageResource.

`imageio.core.Format.__init__`

`Format.__init__(name: str, description: str, extensions=None, modes: Optional[str] = None) → None`

Initialize the Plugin.

Parameters

name [str] A short name of this format. Users can select a format using its name.

description [str] A one-line description of the format.

extensions [str | list | None] List of filename extensions that this format supports. If a string is passed it should be space or comma separated. The extensions are used in the documentation

and to allow users to select a format by file extension. It is not used to determine what format to use for reading/saving a file.

modes [str] A string containing the modes that this format can handle ('iIvV'), "i" for an image, "I" for multiple images, "v" for a volume, "V" for multiple volumes. This attribute is used in the documentation and to select the formats when reading/saving a file.

imageio.core.Format._can_read

`Format._can_read(request: imageio.core.request.Request) → bool`

Check if Plugin can read from ImageResource.

This method is called when the format manager is searching for a format to read a certain image. Return True if this format can do it.

The format manager is aware of the extensions and the modes that each format can handle. It will first ask all formats that *seem* to be able to read it whether they can. If none can, it will ask the remaining formats if they can: the extension might be missing, and this allows formats to provide functionality for certain extensions, while giving preference to other plugins.

If a format says it can, it should live up to it. The format would ideally check the `request.firstbytes` and look for a header of some kind.

Parameters

request [Request] A request that can be used to access the ImageResource and obtain metadata about it.

Returns

can_read [bool] True if the plugin can read from the ImageResource, False otherwise.

imageio.core.Format._can_write

`Format._can_write(request: imageio.core.request.Request) → bool`

Check if Plugin can write to ImageResource.

Parameters

request [Request] A request that can be used to access the ImageResource and obtain metadata about it.

Returns

can_read [bool] True if the plugin can write to the ImageResource, False otherwise.

Further, each format contains up to two nested classes; one for reading and one for writing. To support reading and/or writing, the respective classes need to be defined.

For reading, create a nested class that inherits from `imageio.core.Format.Reader` and that implements the following functions:

- Implement `_open(**kwargs)` to initialize the reader. Deal with the user-provided keyword arguments here.
- Implement `_close()` to clean up.
- Implement `_get_length()` to provide a suitable length based on what the user expects. Can be `inf` for streaming data.
- Implement `_get_data(index)` to return an array and a meta-data dict.

- Implement `_get_meta_data(index)` to return a meta-data dict. If index is None, it should return the ‘global’ meta-data.

For writing, create a nested class that inherits from `imageio.core.Format.Writer` and implement the following functions:

- Implement `_open(**kwargs)` to initialize the writer. Deal with the user-provided keyword arguments here.
- Implement `_close()` to clean up.
- Implement `_append_data(im, meta)` to add data (and meta-data).
- Implement `_set_meta_data(meta)` to set the global meta-data.

4.1.4 Example / template plugin

```
1  # -*- coding: utf-8 -*-
2
3  # imageio is distributed under the terms of the (new) BSD License.
4
5
6
7  """ Example plugin. You can use this as a template for your own plugin.
8
9  """
10
11
12
13  import numpy as np
14
15
16
17  from .. import formats
18
19  from ..core import Format
20
21
22
23
24
25  class DummyFormat(Format):
26
27      """The dummy format is an example format that does nothing.
28
29      It will never indicate that it can read or write a file. When
30
31      explicitly asked to read, it will simply read the bytes. When
32
33      explicitly asked to write, it will raise an error.
34
35
36
37      This documentation is shown when the user does ``help('thisformat')``.
38
```

(continues on next page)

(continued from previous page)

```

Parameters for reading

```

```

-----

```

```

Specify arguments in numpy doc style here.

```

```

Parameters for saving

```

```

-----

```

```

Specify arguments in numpy doc style here.

```

```

"""

```

```

def _can_read(self, request):

```

```

    # This method is called when the format manager is searching
    # for a format to read a certain image. Return True if this format
    # can do it.
    #
    # The format manager is aware of the extensions and the modes
    # that each format can handle. It will first ask all formats
    # that *seem* to be able to read it whether they can. If none
    # can, it will ask the remaining formats if they can: the
    # extension might be missing, and this allows formats to provide
    # functionality for certain extensions, while giving preference
    # to other plugins.
    #
    # If a format says it can, it should live up to it. The format
    # would ideally check the request.firstbytes and look for a

```

(continues on next page)

(continued from previous page)

```

91     # header of some kind.
92
93     #
94
95     # The request object has:
96
97     # request.filename: a representation of the source (only for reporting)
98
99     # request.firstbytes: the first 256 bytes of the file.
100
101     # request.mode[0]: read or write mode
102
103     # request.mode[1]: what kind of data the user expects: one of 'iIvV?'
104
105
106
107     if request.mode[1] in (self.modes + "?"):
108
109         if request.extension in self.extensions:
110
111             return True
112
113
114
115     def _can_write(self, request):
116
117         # This method is called when the format manager is searching
118
119         # for a format to write a certain image. It will first ask all
120
121         # formats that *seem* to be able to write it whether they can.
122
123         # If none can, it will ask the remaining formats if they can.
124
125         #
126
127         # Return True if the format can do it.
128
129
130
131         # In most cases, this code does suffice:
132
133         if request.mode[1] in (self.modes + "?"):
134
135             if request.extension in self.extensions:
136
137                 return True
138
139
140
141     # -- reader
142

```

(continues on next page)

(continued from previous page)

```
143
144
145 class Reader(Format.Reader):
146
147     def _open(self, some_option=False, length=1):
148
149         # Specify kwargs here. Optionally, the user-specified kwargs
150
151         # can also be accessed via the request.kwargs object.
152
153         #
154
155         # The request object provides two ways to get access to the
156
157         # data. Use just one:
158
159         # - Use request.get_file() for a file object (preferred)
160
161         # - Use request.get_local_filename() for a file on the system
162
163         self._fp = self.request.get_file()
164
165         self._length = length # passed as an arg in this case for testing
166
167         self._data = None
168
169
170
171     def _close(self):
172
173         # Close the reader.
174
175         # Note that the request object will close self._fp
176
177         pass
178
179
180
181     def _get_length(self):
182
183         # Return the number of images. Can be np.inf
184
185         return self._length
186
187
188
189     def _get_data(self, index):
190
191         # Return the data and meta data for the given index
192
193         if index >= self._length:
```

(continues on next page)

(continued from previous page)

```

195         raise IndexError("Image index %i > %i" % (index, self._length))
196
197     # Read all bytes
198
199     if self._data is None:
200
201         self._data = self._fp.read()
202
203     # Put in a numpy array
204
205     im = np.frombuffer(self._data, "uint8")
206
207     im.shape = len(im), 1
208
209     # Return array and dummy meta data
210
211     return im, {}
212
213
214
215     def _get_meta_data(self, index):
216
217         # Get the meta data for the given index. If index is None, it
218
219         # should return the global meta data.
220
221         return {} # This format does not support meta data
222
223
224
225     # -- writer
226
227
228
229     class Writer(Format.Writer):
230
231         def _open(self, flags=0):
232
233             # Specify kwargs here. Optionally, the user-specified kwargs
234
235             # can also be accessed via the request.kwargs object.
236
237             #
238
239             # The request object provides two ways to write the data.
240
241             # Use just one:
242
243             # - Use request.get_file() for a file object (preferred)
244
245             # - Use request.get_local_filename() for a file on the system
246

```

(continues on next page)

(continued from previous page)

```

247     self._fp = self.request.get_file()
248
249
250
251     def _close(self):
252
253         # Close the reader.
254
255         # Note that the request object will close self._fp
256
257         pass
258
259
260
261     def _append_data(self, im, meta):
262
263         # Process the given data and meta data.
264
265         raise RuntimeError("The dummy format cannot write image data.")
266
267
268
269     def set_meta_data(self, meta):
270
271         # Process the given meta data (global for all images)
272
273         # It is not mandatory to support this.
274
275         raise RuntimeError("The dummy format cannot write meta data.")
276
277
278
279
280
281 # Register. You register an *instance* of a Format class. Here specify:
282
283 format = DummyFormat(
284
285     "dummy", # short name
286
287     "An example format that does nothing.", # one line descr.
288
289     ".foobar .nonexistenttext", # list of extensions
290
291     "iI", # modes, characters in iIvV
292
293 )
294
295 formats.add_format(format)

```

Becoming a contributor can take as little as 2 minutes (e.g., via a small doc PR) and doesn't require vast coding experience. We are open for contributions in many ways and, if you would like to get involved but aren't sure where to start, create a new issue and we will help you get started. In particular, we are also extremely happy for any help with

- bugfixes,
- improving our documentation,
- improving our DevOp pipeline,
- improving the design of our website,
- new backends/plugins,
- and new features.

Check the relevant section below for a guide on how to get started in any of these areas.

4.2 Small Changes to the Documentation

Note: A small documentation pull request includes changes that only affect a single file. Examples include fixing typos or broken links, rewriting a paragraph for clarity, or adding examples.

A small doc PR is very quick and doesn't require any local setup on your end. All you need is a GitHub account. Here are the steps involved:

1. Navigate to the page you wish to improve.
2. Click on the “Edit this Page” button on the right side pannel.
3. Make your changes to the file that opens.
4. At the bottom of the page under “Commit Changes” choose a descriptive commit message (e.g., “fixed typo in examples”).
5. Click the button “Propose Changes”.
6. That's it. The ImageIO team thanks you for your contribution!

4.3 Large Changes to the Documentation

Installation

For large changes to the documentation, you will have to set up a local development environment with the documentation dependencies installed:

```
# 1. Fork the ImageIO repository
# 2. If you want to use a virtual environment for your setup, create and activate it now.

git clone https://github.com/<replace_by_your_username>/imageio.git
cd imageio
pip install -e .[doc]

# create and checkout a new branch for your contribution
# Note: replace <branch_name> with a descriptive, but short, name
git checkout -b <branch_name>
git push --set-upstream origin <branch_name>

# building the docs locally on Linux or MacOS
```

(continues on next page)

(continued from previous page)

```
# Note: to rebuild the docs, execute this line again
sphinx-build ./docs ./build

# building the docs locally on Windows
# Note: to rebuild the docs, execute this line again
sphinx-build .\docs .\build
```

Developing the PR

Next, you will have to add your modifications to the docs; remember to commit frequently. You are welcome to reach out during this process if you want feedback or have any doubts. Further, you may wish to create a draft PR with your changes, so that we can discuss more easily.

We use sphinx to generate the website and the API has narrative docs. Documentation of the actual functions is autogenerated using numpydoc, and is linked to from the narrative API docs. Further, the list of supported formats, too, is autogenerated using a custom sphinx extension (`imageio_ext.py`); essentially, it parses the respective format RST files using jinja and inserts the formats from `imageio.config.known_extensions`.

Submitting the PR

Once you are happy with your changes, push your changes to your local fork, head over to the [main repo](#) and create a new PR. In the description, briefly summarize what the changes are about (there is no fixed format). If we discussed them before in an issue, add a reference to that issue, so that we can track it. From there, we will help you by reviewing your changes, discussing any changes and eventually merging your work into ImageIO.

Thank you for contributing!

4.4 Fixing a Bug

Note: We currently don't have a dedicated maintainer that uses MacOS as their primary development platform. If you would like to suggest yourself, please get in touch, e.g., via a new issue.

The first step to fixing a bug is to open a new issue that describes the bug (ideally including a [mwe](https://en.wikipedia.org/wiki/Minimal_working_example)) to discuss where the fix should live. Alternatively, if an issue already exists, leave a comment to let us know you want to work on it.

In general, a bugfix follows the usual open-source routine. Here is a rough outline:

```
# Fork the ImageIO repository

git clone https://github.com/<replace_by_fork_location>/imageio.git
cd imageio

# Note: replace <plugin_name> with the plugin that has the bug to
#       install optional dependencies
pip install -e .[dev,<plugin_name>]

# Note: replace <branch_name> with a descriptive, but short, name
git checkout -b <branch_name>
git push --set-upstream origin <branch_name>

pytest # run the existing test suite to verify install
```

(continues on next page)

(continued from previous page)

```
# Add a unit test that reproduces the faulty behavior

# Apply the changes to fix the bug. Remember to commit frequently.

# check if your changes are covered by tests
coverage run -m pytest
coverage report -m

# If changes are not fully covered, add test(s) to cover the
# missing branches.

# Submit a PR. In the description, reference the abovementioned
# issue and give a brief description of the changes.
```

Thank you for contributing!

4.5 Adding a new Feature

Note: We currently don't have a dedicated maintainer that uses MacOS as their primary development platform. If you would like to suggest yourself, please get in touch, e.g., via a new issue.

The first step to contributing a new feature is to open a new issue on our issue page so we can discuss how the feature should look like, if it can work with the relevant backends, and fits within the scope of the library.

Once that is out of the way, the procedure usually follows the following steps:

```
# Fork the ImageIO repository

git clone https://github.com/<replace_by_fork_location>/imageio.git
cd imageio

# Note: replace <plugin_name> with the plugin that has the bug to
#       install optional dependencies
pip install -e .[dev,<plugin_name>]

# Note: replace <branch_name> with a descriptive, but short, name
git checkout -b <branch_name>
git push --set-upstream origin <branch_name>

pytest # run the existing test suite to verify install

# Add the desired/discussed functionality

# For each new function you've created add a descriptive docstring
# compliant with numpydoc

# Add an example to ``docs/examples.rst`` showing off the new
# feature
```

(continues on next page)

(continued from previous page)

```
# Add unit tests to verify that the feature does what it is
# intended to do

# check if your changes are covered by tests
coverage run -m pytest
coverage report -m

# If changes are not fully covered, add test(s) to cover the
# missing branches.

# Submit a PR. In the description, reference the feature issue and
# give a brief description of the changes.
```

Thank you for contributing!

4.6 Webdesign

Warning: We currently don't have a dedicated maintainer for this area. If you would like to suggest yourself, please get in touch, e.g., via a new issue.

There is currently no established way of suggestion webdesign related changes. If you have any suggestions regarding

- the structure/layout of the docs
- improvements of the template or its config
- styling of the website
- (other webdesign related items)

Please open a new issue and we will discuss with you.

4.7 DevOps

Before you go and improve our tooling, please start by first opening a new issue and discussing your idea with us. We ask this, because we want to make sure that there is at least one maintainer familiar with the technology you want to use. If anything breaks in the CI/CD pipeline, it will have a direct impact on our release cycle, and we would like to make sure that at least one maintainer is able to step in and fix it in a timely fashion.

Installation

While you may be able to complete some devops related contributions in GitHub itself, a local setup will perform better in most situations:

```
# 1. Fork the ImageIO repository

git clone https://github.com/<replace_by_your_username>/imageio.git
cd imageio
pip install -e .
```

(continues on next page)

(continued from previous page)

```
# create and checkout a new branch for your contribution
# Note: replace <branch_name> with a descriptive, but short, name
git checkout -b <branch_name>
git push --set-upstream origin <branch_name>
```

Developing the PR

Do your changes, and remember to commit frequently. If you want to test your changes against our CI/CD provider (GH Actions), you can submit a draft PR, which we will review and run. Alternatively, you configure your local fork to execute actions and develop against it. You can find our workflows in the `.github` folder.

Continuous Integration (CI): The core of our CI is a matrix test across all major OSes and supported python versions running a testsuite based on `pytest`. Additionally, we track linting errors (`black` + `flake8`), coverage (`codecov`), and have `readthedocs` build a preview of the documentation.

Continuous Deployment (CD): Our continuous deployment pipeline checks weekly (Monday night, EU time) for any changes to the repository. If there are any, it uses `python-semantic-release` to figure out if the version should bump and a new release should be made. If so, all tests are run against the master branch, the version is bumped, and a new release is made and published to GitHub and PyPI. Further, we have a feedstock on `conda-forge` which manages releases to `conda`.

Submitting the PR

Once you are happy with your changes, push your changes to your local fork, head over to the [main repo](#) and create a new PR. In the description, briefly summarize what the changes are about (there is no fixed format) and add a reference to the issue in which we discussed them. From there, we will help you by reviewing your changes, discussing them and eventually merging your work into ImageIO.

Thank you for contributing!

4.8 Implementing a new Plugin

Plugins allow integration of a new backends into ImageIO. They can exist independently of ImageIO; however, we encourage you to contribute any plugins back upstream. This way others, too, can benefit from using the new backend and you will get compatibility guarantees by virtue of the backend becoming part of our test suite.

Note: These instructions assume that you indeed wish to contribute the plugin.

If you don't, then you won't need a dev installation of ImageIO and can write the plugin directly. In this case, you will have to pass the plugin class to API calls using the plugin kwarg. For example:

```
import imageio as iio
from my_plugin import PluginClass

iio.imread(ImageResource, plugin=PluginClass)
```

Installation

To develop a new plugin, you can start off with a simple def install:

```
# 1. Fork the ImageIO repository

git clone https://github.com/<replace_by_your_username>/imageio.git
```

(continues on next page)

(continued from previous page)

```

cd imageio
pip install -e .[dev]

# create and checkout a new branch for your contribution
# Note: replace <branch_name> with a descriptive, but short, name
git checkout -b <branch_name>
git push --set-upstream origin <branch_name>

# verify installation
pytest

```

Develop the Plugin

To write a new plugin, you have to create a new class that follows our plugin API, which is documented below:

<code>imageio.plugins</code>	Here you can find documentation on how to write your own plugin to allow ImageIO to access a new backend.
<code>imageio.core.v3_plugin_api.PluginV3(request)</code>	A ImageIO Plugin.

4.8.1 imageio.core.v3_plugin_api.PluginV3

class `imageio.core.v3_plugin_api.PluginV3(request: imageio.core.request.Request)`

A ImageIO Plugin.

This is an abstract plugin that documents the v3 plugin API interface. A plugin is an adapter/wrapper around a backend that converts a request from `iio.core` (e.g., read an image from file) into a sequence of instructions for the backend that fulfill the request.

Plugin authors may choose to subclass this class when implementing a new plugin, but aren't obliged to do so. As long as the plugin class implements the interface (methods) described below the ImageIO core will treat it just like any other plugin.

Parameters

request [`iio.Request`] A request object that represents the users intent. It provides a standard interface to access the various `ImageResources` and serves them to the plugin as a file object (or file). Check the docs for details.

****kwargs** [Any] Additional configuration arguments for the plugin or backend. Usually these match the configuration arguments available on the backend and are forwarded to it.

Raises

InitializationError During `__init__` the plugin tests if it can fulfill the request. If it can't, e.g., because the request points to a file in the wrong format, then it should raise an `InitializationError` and provide a reason for failure. This reason may be reported to the user.

ImportError Plugins will be imported dynamically when listed in `iio.config.known_plugins` to fulfill requests. This way, users only have to load plugins/backends they actually use. If this plugin's backend is not installed, it should raise an `ImportError` either during module import or during class construction.

Notes

Upon successful construction the plugin takes ownership of the provided request. This means that it is the plugin's responsibility to call `request.finish()` to close the resource when it is no longer needed.

Plugins `_must_` implement a context manager that closes and cleans any resources held by the plugin upon exit.

Attributes

request

Methods

<code>close()</code>	Close the ImageResource.
<code>iter()</code>	Iterate the ImageResource.
<code>metadata([index, exclude_applied])</code>	Format-Specific ndimage metadata.
<code>properties([index])</code>	Standardized ndimage metadata.
<code>read(*[, index])</code>	Read a ndimage.
<code>write(ndimage)</code>	Write a ndimage to a ImageResource.

Attribute and Method Details

request

close() → None

Close the ImageResource.

This method allows a plugin to behave similar to the python build-in `open`:

```
image_file = my_plugin(Request, "r")
...
image_file.close()
```

It is used by the context manager and deconstructor below to avoid leaking ImageResources. If the plugin has no other cleanup to do it doesn't have to overwrite this method itself and can rely on the implementation below.

iter() → `numpy.ndarray`

Iterate the ImageResource.

This method returns a generator that yields ndimages in the order in which they appear in the file. This is roughly equivalent to:

```
idx = 0
while True:
    try:
        yield self.read(index=idx)
    except ValueError:
        break
```

It works very similar to `read`, and you can consult the documentation of that method for additional information on desired behavior.

Parameters

****kwargs** [Any] The iter method may accept any number of plugin-specific keyword arguments to further customize the reading/iteration behavior. Usually these match the arguments available on the backend and are forwarded to it.

Yields

ndimage [np.ndarray] A ndimage containing decoded pixel data (sometimes called bitmap).

See also:

[PluginV3.read](#)

metadata(*index: int = 0, exclude_applied: bool = True*) → Dict[str, Any]

Format-Specific ndimage metadata.

The method reads metadata stored in the ImageResource and returns it as a python dict. The plugin is free to choose which name to give a piece of metadata; however, if possible, it should match the name given by the format. There is no requirement regarding the fields a plugin must expose; however, if a plugin does expose any, `exclude_applied` applies to these fields.

If the plugin does return metadata items, it must check the value of `exclude_applied` before returning them. If `exclude_applied` is True, then any metadata item that would be applied to an ndimage returned by `read` (or `iter`) must not be returned. This is done to avoid confusion; for example, if an ImageResource defines the ExIF rotation tag, and the plugin applies the rotation to the data before returning it, then `exclude_applied` prevents confusion on whether the tag was already applied or not.

The *kwarg* `index` behaves similar to its counterpart in `read` with one exception: If the `index` is None, then global metadata is returned instead of returning a combination of all metadata items. If there is no global metadata, the Plugin should return an empty dict or raise an exception.

Parameters

index [int] The index of the ndimage to read. If the index is out of bounds a `ValueError` is raised. If None, global metadata is returned.

exclude_applied [bool] If True (default), do not report metadata fields that the plugin would apply/consume while reading the image.

Returns

metadata [dict] A dictionary filled with format-specific metadata fields and their values.

properties(*index: int = 0*) → imageio.core.v3_plugin_api.ImageProperties

Standardized ndimage metadata.

Parameters

index [int] The index of the ndimage for which to return properties. If the index is out of bounds a `ValueError` is raised. If None, return the properties for the ndimage stack. If this is impossible, e.g., due to shape mismatch, an exception will be raised.

Returns

properties [ImageProperties] A dataclass filled with standardized image metadata.

read(**, index: int = 0*) → numpy.ndarray

Read a ndimage.

The read method loads a (single) ndimage, located at `index` from the requested ImageResource.

It is at the plugin's discretion to decide (and document) what constitutes a single ndimage. A sensible way to make this decision is to choose based on the ImageResource's format and on what users will expect from such a format. For example, a sensible choice for a TIFF file produced by an ImageJ hyperstack is to read

it as a volumetric ndimage (1 color dimension followed by 3 spatial dimensions). On the other hand, a sensible choice for a MP4 file produced by Davinci Resolve is to treat each frame as a ndimage (2 spatial dimensions followed by 1 color dimension).

The value `index=None` is special. It requests the plugin to load all ndimages in the file and stack them along a new first axis. For example, if a MP4 file is read with `index=None` and the plugin identifies single frames as ndimages, then the plugin should read all frames and stack them into a new ndimage which now contains a time axis as its first axis. If a PNG file (single image format) is read with `index=None` the plugin does a very similar thing: It loads all ndimages in the file (here it's just one) and stacks them along a new first axis, effectively prepending an axis with size 1 to the image. If a plugin does not wish to support `index=None` it should set a more sensible default and raise a `ValueError` when requested to read using `index=None`.

Parameters

index [int] The index of the ndimage to read. If the index is out of bounds a `ValueError` is raised. If `None`, the plugin reads all ndimages in the file and stacks them along a new, prepended, batch dimension. If stacking is impossible, e.g., due to shape mismatch, an exception will be raised.

****kwargs** [Any] The read method may accept any number of plugin-specific keyword arguments to further customize the read behavior. Usually these match the arguments available on the backend and are forwarded to it.

Returns

ndimage [np.ndarray] A ndimage containing decoded pixel data (sometimes called bitmap).

Notes

The `ImageResource` from which the plugin should read is managed by the provided request object. Directly accessing the managed `ImageResource` is `_not_` permitted. Instead, you can get `FileLike` access to the `ImageResource` via `request.get_file()`.

If the backend doesn't support reading from `FileLike` objects, you can request a temporary file to pass to the backend via `request.get_local_filename()`. This is, however, not very performant (involves copying the Request's content into a temporary file), so you should avoid doing this whenever possible. Consider it a fallback method in case all else fails.


```

write(ndimage: Union[Sequence[Sequence[Sequence[Sequence[Sequence[Any]]]],
    numpy.typing._array_like._SupportsArray[numpy.dtype],
    Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]],
    Sequence[Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]]],
    Sequence[Sequence[Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]]]],
    Sequence[Sequence[Sequence[Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]]]]],
    bool, int, float, complex, str, bytes, Sequence[Union[bool, int, float, complex, str, bytes]],
    Sequence[Sequence[Union[bool, int, float, complex, str, bytes]]],
    Sequence[Sequence[Sequence[Union[bool, int, float, complex, str, bytes]]]],
    Sequence[Sequence[Sequence[Sequence[Union[bool, int, float, complex, str, bytes]]]]],
    List[Union[Sequence[Sequence[Sequence[Sequence[Sequence[Sequence[Any]]]],
    numpy.typing._array_like._SupportsArray[numpy.dtype],
    Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]],
    Sequence[Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]]],
    Sequence[Sequence[Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]]]],
    Sequence[Sequence[Sequence[Sequence[numpy.typing._array_like._SupportsArray[numpy.dtype]]]]],
    bool, int, float, complex, str, bytes, Sequence[Union[bool, int, float, complex, str, bytes]],
    Sequence[Sequence[Union[bool, int, float, complex, str, bytes]]],
    Sequence[Sequence[Sequence[Union[bool, int, float, complex, str, bytes]]]],
    Sequence[Sequence[Sequence[Sequence[Union[bool, int, float, complex, str, bytes]]]]]]]]]) →
Optional[bytes]

```

Write a ndimage to a ImageResource.

The `write` method encodes the given ndimage into the format handled by the backend and writes it to the ImageResource. It overwrites any content that may have been previously stored in the file.

If the backend supports only a single format then it must check if the ImageResource matches that format and raise an exception if not. Typically, this should be done during initialization in the form of a `InitializationError`.

If the backend supports more than one format it must determine the requested/desired format. Usually this can be done by inspecting the ImageResource (e.g., by checking `request.extension`), or by providing a mechanism to explicitly set the format (perhaps with a - sensible - default value). If the plugin can not determine the desired format, it **must not** write to the ImageResource, but raise an exception instead.

If the backend supports at least one format that can hold multiple ndimages it should be capable of handling ndimage batches and lists of ndimages. If the `ndimage` input is a list of ndimages, the plugin should not assume that the ndimages are not stackable, i.e., ndimages may have different shapes. Otherwise, the `ndimage` may be a batch of multiple ndimages stacked along the first axis of the array. The plugin must be able to discover this, either automatically or via additional *kwargs*. If there is ambiguity in the process, the plugin must clearly document what happens in such cases and, if possible, describe how to resolve this ambiguity.

Parameters

ndimage [ArrayLike] The ndimage to encode and write to the current ImageResource.

****kwargs** [Any] The write method may accept any number of plugin-specific keyword arguments to customize the writing behavior. Usually these match the arguments available on the backend and are forwarded to it.

Returns

encoded_image [bytes or None] If the chosen ImageResource is the special target "<bytes>" then write should return a byte string containing the encoded image data. Otherwise, it returns None.

Notes

The ImageResource to which the plugin should write to is managed by the provided request object. Directly accessing the managed ImageResource is `_not_` permitted. Instead, you can get FileLike access to the ImageResource via `request.get_file()`.

If the backend doesn't support writing to FileLike objects, you can request a temporary file to pass to the backend via `request.get_local_filename()`. This is, however, not very performant (involves copying the Request's content from a temporary file), so you should avoid doing this whenever possible. Consider it a fallback method in case all else fails.

The file itself should be placed into our plugins folder at `imageio\plugins\your_plugin.py`.

Declare Dependencies

Plugins typically have at least one external dependency: the backend they use to do the decoding/encoding. This dependency (and any others a plugin may have) have to be declared in our `setup.py`.

All plugins start out as optional dependencies (but may be promoted if they turn out stable and useful ;)). As such, to declare dependencies of a plugin add an item to the `extra_requires` dict. The key name typically matches the name of the backend, and the value is a list of dependencies:

```
extras_require = {
    # ...
    "my_backend": ["my_backend", ...],
}
```

That said, a plugin can assume that its dependencies are installed, i.e., it doesn't have to explicitly assert that imports resolve. We catch any `ImportError` internally and use it to inform the user that they have to install missing dependencies via:

```
pip install imageio[my_backend]
```

Register the Plugin

Registering the plugin with ImageIO enables various kinds of auto-magic. Currently this involves two steps:

1. Register the plugin as a `known_plugin`
2. Associate supported extensions with the plugin

First, add the plugin to the list of known plugins. This allows ImageIO to try the plugin in case no better suited one can be found and also enables all other optimizations. For this, add a new item to the dict in `imageio.config.plugins.py`. The key is the name under which the plugin will be known (usually the name of the backend) and the value is an instance of `PluginConfig`, for example:

```
known_plugins["my_plugin"] = PluginConfig(
    name="my_plugin", # (same as key)
    class_name="MyPluginClass", # the name of the class
    module_name="imageio.plugins.my_plugin" # where the class is implemented
    is_legacy: bool = True, # True if plugin follows V2 API
    install_name: str = "my_backend", # name of the optional dependency
)
```

For more details on the `PluginConfig` class, check the classes docstring.

Second, if the plugin adds support for any new formats that were not previously supported by ImageIO, declare those formats in `imageio.config.extensions.py`. For this, add items to the `extension_list`; items are instances of the `FileExtension` class:

```
FileExtension(
    name="Full Name of Format",
    extension=".file_extension", # e.g. ".png"
    priority=["my_plugin"], # a list of plugins that supports reading this format
),
```

Plugins listed in `priority` are assumed to be able to read the declared format. Further, ImageIO will prefer plugins that appear earlier over plugins that appear later in the list, i.e., they are tried first.

Finally, for each format that is already supported by other plugins, add the new plugin at the end of the `priority` list. (This avoids breaking existing downstream code.)

Document the Plugin

```
# build the docs
sphinx-build ./docs ./build # MacOS / Linux
sphinx-build .\docs .\build # Windows
```

Beyond the plugin itself, you will have to write documentation for it that tells others what features are available and how to use it. In ImageIO classes are documented using `numpydoc`, so they should follow `numpy`'s documentation style. Most importantly, you will have to add a module docstring to the plugin file (check the other plugins for examples), which will be used as the entrypoint for your plugin's documentation.

Once you have written something, hook the documentation into our docs. For this add its import path (`imageio.plugins.your_module_name`) in `docs\reference\index.rst`. It should be inside the `autosummary` block that lists all plugins.

Test the Plugin

```
# run tests
pytest # run all
pytest path/to/test/file.py # run specific module
pytest path/to/test/file.py::test_name_of_test # run specific test

# check coverage
coverage run -m pytest # update the coverage logs
coverage report -m # report coverage in shell
```

To test your plugin, create a new test file at `tests\test_myplugin.py`. In the file, define functions that have their name begin with `test_` (example: `def test_png_reading():`) and fill them with code that uses your plugin.

Our main requirement for tests of new plugins is that they cover the full plugin. Ideally, they also test reading and writing of all supported formats, but this is not strictly necessary. Check the commands above for how to run tests and check test coverage of your plugin.

Submitting the PR

Once you are happy with the plugin, push your changes to your local fork, head over to the [main repo](#) and create a new PR. In the description, briefly summarize what the plugin does (there is no fixed format) and, if it exists, add a reference to the issue in which the plugin is discussed. From there, we will help you by reviewing your changes, discussing them and eventually merging your plugin into ImageIO.

Thank you for contributing!

4.9 Adding a missing Format

Adding a new format (or updating an existing one) can be done directly in GitHub. Navigate to [this page](<https://github.com/imageio/imageio/blob/master/imageio/config/extensions.py>) and click on the “edit this file” button (looks like a pen). From here, either edit the existing format, e.g., by adding a new backend that supports it in `priority`, or by add a new format. For this add this snippet to the bottom of the `extension_list`:

```
FileExtension(  
    name="<Full Name of File Format>", # e.g., Hasselblad raw  
    extension="<extension>", # e.g., .3fr  
    priority=<list of supporting backend names>, # e.g., ["RAW-FI"]  
)
```

Thank you for contributing!

4.10 Full Developer Setup

Note: This section is intended for library maintainers and people that plan to make multiple contributions of various kinds.

If you plan to make a series of contributions, we recommend a development installation with all plugins:

```
# 1. Fork the ImageIO repository  
# 2. Optional: Create and activate your virtual environment of choice  
  
# install  
git clone https://github.com/<replace_by_fork_location>/imageio.git  
cd imageio  
pip install -e .[full]  
  
# download test images and run all tests  
pytest  
  
# build the docs  
sphinx-build ./docs ./build # MacOS / Linux  
sphinx-build .\docs .\build # Windows  
  
# check coverage  
coverage run -m pytest # update the coverage logs  
coverage report -m # report coverage in shell
```

PYTHON MODULE INDEX

i

- `imageio, ??`
- `imageio.plugins, 49`
- `imageio.plugins.bsdf, 32`
- `imageio.plugins.dicom, 33`
- `imageio.plugins.feisem, 33`
- `imageio.plugins.ffmpeg, 34`
- `imageio.plugins.fits, 35`
- `imageio.plugins.freeimage, 36`
- `imageio.plugins.gdal, 36`
- `imageio.plugins.lytro, 37`
- `imageio.plugins.npz, 37`
- `imageio.plugins.pillow, 37`
- `imageio.plugins.pillow_legacy, 39`
- `imageio.plugins.simpleitk, 42`
- `imageio.plugins.spe, 42`
- `imageio.plugins.swf, 44`
- `imageio.plugins.tiffiff, 45`

Symbols

`__init__()` (*imageio.core.Format* method), 52
`_can_read()` (*imageio.core.Format* method), 53
`_can_write()` (*imageio.core.Format* method), 53

A

`append_data()` (*imageio.core.format.Writer* method), 31

C

`can_read()` (*imageio.core.Format* method), 50
`can_write()` (*imageio.core.Format* method), 50
`close()` (*imageio.core.format.Reader* method), 30
`close()` (*imageio.core.format.Writer* method), 31
`close()` (*imageio.core.v3_plugin_api.PluginV3* method), 66
`closed` (*imageio.core.format.Reader* property), 30
`closed` (*imageio.core.format.Writer* property), 31

D

`description` (*imageio.core.Format* attribute), 50
`doc` (*imageio.core.Format* attribute), 50

E

`extension` (*imageio.core.Request* attribute), 51
`extensions` (*imageio.core.Format* attribute), 50

F

`filename` (*imageio.core.Request* attribute), 51
`finish()` (*imageio.core.Request* method), 52
`firstbytes` (*imageio.core.Request* attribute), 51
`Format` (class in *imageio.core*), 49
`format` (*imageio.core.format.Reader* property), 30
`format` (*imageio.core.format.Writer* property), 31
`format_hint` (*imageio.core.Request* attribute), 51

G

`get_data()` (*imageio.core.format.Reader* method), 30
`get_file()` (*imageio.core.Request* method), 52
`get_length()` (*imageio.core.format.Reader* method), 30

`get_local_filename()` (*imageio.core.Request* method), 52
`get_meta()` (*imageio.plugins.pillow.PillowPlugin* method), 39
`get_meta_data()` (*imageio.core.format.Reader* method), 30
`get_next_data()` (*imageio.core.format.Reader* method), 30
`get_reader()` (*imageio.core.Format* method), 50
`get_reader()` (in module *imageio*), 29
`get_result()` (*imageio.core.Request* method), 52
`get_writer()` (*imageio.core.Format* method), 50
`get_writer()` (in module *imageio*), 29

H

`help()` (in module *imageio*), 25

I

`imageio`
 module, 1
`imageio.plugins`
 module, 49
`imageio.plugins.bsdf`
 module, 32
`imageio.plugins.dicom`
 module, 33
`imageio.plugins.feisem`
 module, 33
`imageio.plugins.ffmpeg`
 module, 34
`imageio.plugins.fits`
 module, 35
`imageio.plugins.freeimage`
 module, 36
`imageio.plugins.gdal`
 module, 36
`imageio.plugins.lytro`
 module, 37
`imageio.plugins.npz`
 module, 37
`imageio.plugins.pillow`
 module, 37

`imageio.plugins.pillow_legacy`
 module, 39
`imageio.plugins.simpleitk`
 module, 42
`imageio.plugins.spe`
 module, 42
`imageio.plugins.swf`
 module, 44
`imageio.plugins.tiffiffle`
 module, 45
`imread()` (in module `imageio`), 26
`imwrite()` (in module `imageio`), 28
`iter()` (`imageio.core.v3_plugin_api.PluginV3` method), 66
`iter()` (`imageio.plugins.pillow.PillowPlugin` method), 39
`iter_data()` (`imageio.core.format.Reader` method), 31

K

`kwargs` (`imageio.core.Request` attribute), 52

M

`metadata()` (`imageio.core.v3_plugin_api.PluginV3` method), 67
`mimread()` (in module `imageio`), 26
`mimwrite()` (in module `imageio`), 28
`mode` (`imageio.core.Request` attribute), 52
`modes` (`imageio.core.Format` attribute), 50
`module`
 `imageio`, 1
 `imageio.plugins`, 49
 `imageio.plugins.bsdf`, 32
 `imageio.plugins.dicom`, 33
 `imageio.plugins.feisem`, 33
 `imageio.plugins.ffmpeg`, 34
 `imageio.plugins.fits`, 35
 `imageio.plugins.freeimage`, 36
 `imageio.plugins.gdal`, 36
 `imageio.plugins.lytro`, 37
 `imageio.plugins.npz`, 37
 `imageio.plugins.pillow`, 37
 `imageio.plugins.pillow_legacy`, 39
 `imageio.plugins.simpleitk`, 42
 `imageio.plugins.spe`, 42
 `imageio.plugins.swf`, 44
 `imageio.plugins.tiffiffle`, 45
`mvolread()` (in module `imageio`), 27
`mvolwrite()` (in module `imageio`), 29

N

`name` (`imageio.core.Format` attribute), 50

P

`PluginV3` (class in `imageio.core.v3_plugin_api`), 65

`properties()` (`imageio.core.v3_plugin_api.PluginV3` method), 67

R

`read()` (`imageio.core.v3_plugin_api.PluginV3` method), 67
`read()` (`imageio.plugins.pillow.PillowPlugin` method), 38
`Reader` (class in `imageio.core.format`), 30
`Reader` (`imageio.core.Format` attribute), 50
`Request` (class in `imageio.core`), 51
`request` (`imageio.core.format.Reader` property), 31
`request` (`imageio.core.format.Writer` property), 31
`request` (`imageio.core.v3_plugin_api.PluginV3` attribute), 66

S

`set_image_index()` (`imageio.core.format.Reader` method), 31
`set_meta_data()` (`imageio.core.format.Writer` method), 31
`show_formats()` (in module `imageio`), 25

V

`volread()` (in module `imageio`), 27
`volwrite()` (in module `imageio`), 28

W

`write()` (`imageio.core.v3_plugin_api.PluginV3` method), 68
`write()` (`imageio.plugins.pillow.PillowPlugin` method), 38
`Writer` (class in `imageio.core.format`), 31
`Writer` (`imageio.core.Format` attribute), 50